

## DATA SHEET

## Code: ETI-D02/40A FUSE LINK **ETI-D02/40A** 40 A 400 V gL/gG E18 ETI



Fuse-links are used as the most reliable protection of electrical installation against overload and short-circuit currents. All fuse-links have blown-fuse indicators which are visible through the screw cap when mounted.

Rated current:	40 A
Rated voltage:	250 V DC, 400 V AC
Fusing characteristics:	gL/gG
Fuse base:	E18
Туре:	D0
Size:	D02
Breaking capacity:	50 kA AC, 8 kA DC
Main features:	<ul> <li>Low power and energy losses</li> <li>Small temperature increase</li> <li>High ability to limit short-circuit current</li> <li>Stability of current-time characteristics and full selectivity of operation</li> <li>Selective cooperation with over-current circuit breakers</li> </ul>
Housing:	Ceramic
Weight:	0.013 kg
Dimensions:	Ø 15 x 36 mm Ø 13.3 mm (A)
Manufacturer / Brand:	ETI
Guarantee:	2 years



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60