

Code: MCT82M-BK

## PROXIMITY READER **MCT82M-BK** ROGER

Indoor reader of proximity cards and key-fobs designed to work in the RACS 5 access control and building automation system. 13.56 MHz S50 standard.



|                                |                                                                                                                                                                                            |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Support:                       | RACS 5 (Roger)                                                                                                                                                                             |
| Cards support:                 | 13.56 MHz S50                                                                                                                                                                              |
| Reading distance of prox-keys: | max. 7 cm                                                                                                                                                                                  |
| Keyboard built-in:             | —                                                                                                                                                                                          |
| Autonomous operation:          | —                                                                                                                                                                                          |
| Doorbell button:               | —                                                                                                                                                                                          |
| Tamper output:                 | ✓                                                                                                                                                                                          |
| Communication:                 | RS-485                                                                                                                                                                                     |
| Main features:                 | <ul style="list-style-type: none"> <li>• Tamper protection (detection of removing from mounting surface and enclosure opening)</li> <li>• LED indication</li> <li>• Beep signal</li> </ul> |
| Power supply:                  | 10 ... 15 V DC                                                                                                                                                                             |
| Average current consumption:   | 60 mA                                                                                                                                                                                      |
| Operation temp:                | -10 °C ... 50 °C                                                                                                                                                                           |



## DATA SHEET

|                                |                              |
|--------------------------------|------------------------------|
| Permissible relative humidity: | 10 ... 95 % (non-condensing) |
| "Index of Protection":         | IP41                         |
| Weight:                        | 0.1 kg                       |
| Dimensions:                    | 85 x 85 x 22 mm              |
| Manufacturer / Brand:          | ROGER                        |
| Guarantee:                     | <b>3 years</b>               |