

Code: MCT62E

## PROXIMITY READER **MCT62E** ROGER

Outdoor reader of proximity cards and key-fobs designed to work in the RACS 5 access control and building automation system. Unique 125 kHz standard.



|                                |                                                                                                                                                                                            |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Support:                       | RACS 5 (Roger)                                                                                                                                                                             |
| Cards support:                 | Unique EM 125kHz                                                                                                                                                                           |
| Reading distance of prox-keys: | max. 8 cm                                                                                                                                                                                  |
| Keyboard built-in:             | —                                                                                                                                                                                          |
| Autonomous operation:          | —                                                                                                                                                                                          |
| Doorbell button:               | —                                                                                                                                                                                          |
| Tamper output:                 | ✓                                                                                                                                                                                          |
| Communication:                 | RS-485 - RACS 5 (Roger)                                                                                                                                                                    |
| Main features:                 | <ul style="list-style-type: none"> <li>• Tamper protection (detection of removing from mounting surface and enclosure opening)</li> <li>• LED indication</li> <li>• Beep signal</li> </ul> |
| Power supply:                  | 11 ... 15 V DC                                                                                                                                                                             |
| Average current consumption:   | 50 mA                                                                                                                                                                                      |
| Operation temp:                | -25 °C ... 60 °C                                                                                                                                                                           |



## DATA SHEET

|                                |                              |
|--------------------------------|------------------------------|
| Permissible relative humidity: | 10 ... 95 % (non-condensing) |
| "Index of Protection":         | IP65                         |
| Weight:                        | 0.08 kg                      |
| Dimensions:                    | 100 x 40 x 25 mm             |
| Manufacturer / Brand:          | ROGER                        |
| Guarantee:                     | <b>3 years</b>               |

