

Code: DH-IPC-HDW8341X-3D

IP CAMERA **DH-IPC-HDW8341X-3D** - 3.0 Mpx, 2.8 mm DAHUA

The Dahua Stereo Vision Counting Camera uses imaging from two sensors to detect people and real-time tracking and behaviour analysis. PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.



Standard:	TCP/IP
Sensor:	2 x 1/2.8 " STARVIS™ CMOS
Matrix size:	2 x 3.0 Mpx
Scanning system:	Progressive
Resolution:	2048 x 1536 - 3.0 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
Lens:	2 x 2.8 mm / F1.8
View angle:	137 ° (horizontal) 114 ° (vertical)
Range of IR illumination:	10 m
S/N ratio:	> 50 dB
RS-485 interface:	—
Image compression method:	H.265 / H.264
Alarm inputs / outputs:	2 / 2



DATA SHEET

Audio:	• 2 x External microphone input • Microphone built-in • Audio output • Bi-directional audio streaming support
Bitrate:	80 ... 6144 kbps @ H.265 192 ... 10240 kbps @ H.264
Main stream frame rate:	25 fps @ 3.1 Mpx
Network interface:	10/100 Base-T (RJ-45)
Network protocols:	HTTP, HTTPS, TCP, ARP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, IPv4/IPv6, QoS, UPnP, NTP, Bonjour, IEEE 802.1x, Multicast, ICMP, IGMP, SNMP, TLS
Memory card slot:	Micro SD memory cards up to 128GB support (possible local recording)
Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Default IP address:	192.168.1.108
Default admin user / password:	admin / admin
Web browser access ports:	80, 37777
PC client access ports:	37777
Mobile client access ports:	37777
Port ONVIF:	80
RTSP URL:	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
WEB Server:	Built-in
Max. number of on-line users:	20
ONVIF:	16.12
Main features:	• IVS analysis - Target Count, line crossing people counting, region people counting • Heat map - the selection in the image by corresponding colors the areas with different traffic • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • Possibility to change the resolution, quality and bit rate • ROI - improve the quality of selected parts of image • Time mark and image description • Configurable: brightness, contrast, saturation • Privacy zones • Motion Detection • Power output 12 V DC
Power supply:	• PoE (802.3af) • 12 V DC / 1000 mA
Power consumption:	< 12 W
Housing:	Compact, Metal
Color:	White

Vandal-proof:	—
"Index of Protection":	IP67
Operation temp:	-30 °C ... 60 °C
Weight:	0.82 kg
Dimensions:	204 x 78 x 62 mm
Supported languages:	English
Manufacturer / Brand:	DAHUA
Guarantee:	3 years