

Code: AT-UPS650-LED

UPS **AT-UPS650-LED** 650 VA EAST

The AT-UPS650-LED UPS has been equipped with a number of advanced technologies ensuring active monitoring of the power supply network. The device works with power supply adapters having Active Power Factor Correction (APFC).



Nominal power:	390 W
Apparent Power:	650 VA
Input voltage:	165 V ... 275 V AC
Input frequency:	50 / 60 Hz (auto detection)
Output voltage:	230 V AC $\pm$ 10 % (Approximated Sine Wave)
Output frequency:	50 / 60 Hz $\pm$ 1 %
Transfer time:	$\leq$ 10 ms
Charging time (recover to 90% capacity):	8 hours
Battery:	1 pcs - 12V/7Ah
Estimated battery operation time:	• 16 minutes @ 100 W • 7 minutes @ 200 W • 4 minutes @ 300 W
Number of outputs:	2 pcs CEE 7/3 (Schuko)

Protections:	• Glass Fuse • Overvoltage • Overload protection • Overcharge protection • Telephone line filter
Operation state indication:	• LED diodes, • Sound signaling
Main features:	• Auto restart while AC is recovering • Automatic Voltage Regulator (AVR) • Compatible with power generators • Remote management - UPSmart application included • Built-in EMI, RFI filter • Configurable alarm
Application:	• Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment
Housing type:	Tower
Operation temp. / Relative humidity:	0 °C ... 40 °C / 20 ... 90 %
Weight:	5.36 kg
Dimensions:	330 x 163 x 95 mm
Manufacturer / Brand:	EAST
Guarantee:	2 years