

Code: DS-KV8102-IM

VIDEO DOORPHONE **DS-KV8102-IM** Hikvision

The device is dedicated to work with Hikvision I generation indoor panels.



Sensor:	1.3 Mpx CMOS
LED illuminator:	—
IR illuminator:	✓
Compatibility:	Hikvision IP Video Doorphones
proximity reader built-in:	Access control cards - 13.56 MHz S50
UTP category:	UTP cat. 5e
Alarm inputs:	4 pcs
Relay outputs:	1 pcs NO/NC
RS-485:	✓
Ethernet:	1 x RJ-45 - 10/100 Base-T
Main features:	• Doorbell button, • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Tamper detection - removing from mounting surface, • Ability to work with reed switch and signalling the door being opened too long



DATA SHEET

Operation temp:	-40 °C ... 70 °C
Power supply:	• 12 V DC / 1 A, • 24 V PoE
Housing:	Aluminum / Plastic, Waterproof
"Index of Protection":	IP65
Color:	Silver
Weight:	0.52 kg
Dimensions:	182 x 100 x 33 mm
Supported languages:	English, Polish, Serbian, Hungarian
Manufacturer / Brand:	Hikvision
SAP Code:	305300105
Guarantee:	3 years