DATA SHEET

Code: DS-K2602

ACCESS CONTROLLER **DS-K2602** Hikvision

The DS-K2602 controller is intended to use in access control systems based on electrical control of door opening.



Number of supported readers:	4 pcs @ RS-485 , 4 pcs @ Wiegand
Battery backup support:	max. 7 Ah
Input lines:	4 pcs - Alarm inputs , 2 pcs - Reed switch , 2 pcs - Door/gate opening button , 5 pcs - Tamper
Output lines:	2 pcs - Lock relay , 4 pcs - Relay
Communication:	• RS-485, • Ethernet, • Wiegand
Power supply:	230 V AC
Main features:	• 100000 indexed users • History of 300000 events • Remote programming from PC • Metal housing
Operation temp:	-20 °C ... 65 °C
Permissible relative humidity:	10 % ... 95 % (non-condensing)

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

DATA SHEET

Weight:	4.61 kg
Dimensions:	370 x 345 x 70 mm
Manufacturer / Brand:	Hikvision
SAP Code:	302900506
Guarantee:	**3 years**

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60