

Code: DS-KIS202

VIDEO DOORPHONE KIT **DS-KIS202** Hikvision

Video Doorphone set of the Hikvision brand with a door station mounted in a surface housing and a 7" colored screen. The DS-KIS202 doesn't need any additional configuration (after connecting according to the diagram the device is ready to operate).
ATTENTION! The device does not support the HIKVISION IP system.



DOOR STATION:	
Sensor:	1/4 " CMOS
IR illuminator:	✓
proximity reader built-in:	—
Video output:	1 Vpp, CVBS - pair of wires compatible with HIKVISION analog video door-phone system
Operation temp:	-30 °C ... 60 °C
Power supply:	12 V DC
Power consumption:	≤ 3 W (operation)
Main features:	• Relay output • 4-wire cable installation : 5 m (included)
Housing:	Aluminum / Plastic, Waterproof
Color:	Black / Silver
"Index of Protection":	IP65
Weight:	0.15 kg
Dimensions:	135 x 49 x 41 mm
INDOOR PANEL:	
Shield:	7 " TFT-LCD color matrix
Resolution:	800 x 480

Main features:	• Plug & Play, • Ultra-flat hands-free monitor, with speakerphone, • Smooth volume control, • Microphone built-in, • Speakers built-in, • Bidirectional communication
Power supply:	12 V DC
Max. current:	420 mA
Power consumption:	≤ 5 W
Operation temp:	-10 °C ... 55 °C
Weight:	0.278 kg
Dimensions:	196 x 133 x 18 mm
Manufacturer / Brand:	Hikvision
SAP Code:	305300619
Guarantee:	3 years