

Code: DS-KM8301

## THE MAIN STATION FOR THE MANAGEMENT OF IP VIDEO DOORPHONES **DS-KM8301** Hikvision

The DS-KM8301 main station is a device allowing for consistent management of a large video doorphone installation. This panel allows contact with any internal panel in the system, support for all door stations and control of the opening of individual gates.

The device has been designed for local access control centres for housing estates or other facilities with a similar number of users. The device cooperates with video doorphones, and other panels working in Hikvision IP standard.

The device is fully configurable via the **iVMS4200** software.



Compatibility:	Interphone installation - Hikvision
Shield:	7 " TFT-LCD color matrix
Resolution:	1024 x 600
Main features:	<ul style="list-style-type: none"> <li>• Microphone built-in,</li> <li>• Speakers built-in,</li> <li>• A handset with a microphone that can be used interchangeably with the hands-free mode,</li> <li>• Built-in camera CMOS 0.3 Mpx,</li> <li>• Bidirectional communication - Audio + Video,</li> <li>• Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume,</li> <li>• IP Hikvision cameras support,</li> <li>• Noise and echo reduction,</li> <li>• The ability of direct communication between two or more panels,</li> <li>• Port RS-485,</li> <li>• Network interface: LAN - 10/100/1000 Base-T,</li> <li>• The device is fully configurable via the <b>iVMS4200</b> software.,</li> <li>• SIP server</li> </ul>
Controlling:	Touch control keys + capacitive touch screen + One-touch action buttons
Default administrator password:	888999
Relay outputs:	2
Power supply:	12 V DC / 830 mA (power adapter included) ,
Color:	Black
Operation temp:	-10 °C ... 55 °C
Weight:	1.92 kg



## DATA SHEET

Dimensions:	436 x 215 x 67 mm
Supported languages:	Polish, English, Serbian, Hungarian
Manufacturer / Brand:	Hikvision
SAP Code:	305300221
Guarantee:	<b>3 years</b>