

Code: DS-7732NI-I4/16P

## NVR **DS-7732NI-I4/16P** 32 CHANNELS + 16-PORT SWITCH POE Hikvision

The DS-7732NI-I4/16P digital recorder is a professional device using in IP surveillance systems. The H.265 / H.264 video compression standard using to record video data, allows to get the best possible quality of recorded image at minimal network transfer and disk storage capacity.



|                                     |                                                                                                                                                                                                                                                                                                                                                    |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standard:                           | TCP/IP                                                                                                                                                                                                                                                                                                                                             |
| Supported resolutions:              | max. 12 Mpx - 4000 x 3000 px                                                                                                                                                                                                                                                                                                                       |
| Video outputs:                      | 1 pcs HDMI 4K<br>1 pcs VGA<br>There is a possibility to configure a SPOT function on one of the output                                                                                                                                                                                                                                             |
| Audio support:                      | 32 Channels - Audio from cameras                                                                                                                                                                                                                                                                                                                   |
| Audio inputs:                       | 1 pcs CINCH - External microphone input                                                                                                                                                                                                                                                                                                            |
| Audio outputs:                      | 1 pcs CINCH                                                                                                                                                                                                                                                                                                                                        |
| Image compression method:           | H.265 / H.265+ / H.264 / H.264+ / MPEG-4                                                                                                                                                                                                                                                                                                           |
| USB:                                | 1 pcs USB 3.0<br>2 pcs USB 2.0                                                                                                                                                                                                                                                                                                                     |
| Supported hard drives:              | 4 x 8 TB SATA                                                                                                                                                                                                                                                                                                                                      |
| Recording modes:                    | Manual, Sensor, Motion detection, Schedule                                                                                                                                                                                                                                                                                                         |
| Network protocols:                  | TCP/IP, DHCP, DNS, DDNS, NTP, SADP, SMTP, NFS, HTTPS, UPnP, iSCSI, Hik Cloud P2P                                                                                                                                                                                                                                                                   |
| External storage devices backup:    | Backup to USB drive (pendrive, external drive)                                                                                                                                                                                                                                                                                                     |
| Searching and playback the records: | Records searching: by time and events type. Records playback: forward, backward, fast, slow                                                                                                                                                                                                                                                        |
| Bitrate:                            | max. 256 Mbps                                                                                                                                                                                                                                                                                                                                      |
| Network functions:                  | <ul style="list-style-type: none"> <li>• Live image view, Playback the records, Backup the records</li> <li>• max. 128 on-line users - iVMS-4200 application</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> </ul> |
| ONVIF:                              | ✓                                                                                                                                                                                                                                                                                                                                                  |
| Mobile phones support:              | Port no.: 8000 or access by a cloud (P2P)<br><ul style="list-style-type: none"> <li>• Android: Free application <a href="#">iVMS-4500</a> or <a href="#">Hik-Connect</a></li> <li>• iOS (iPhone): Free application <a href="#">iVMS-4500</a> or <a href="#">Hik-Connect</a></li> </ul>                                                             |



# DATA SHEET

|                                  |                                                                                                                                                                                                                                       |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Default admin user / password:   | admin / -                                                                                                                                                                                                                             |
| Default IP address:              | DHCP or 192.168.1.64                                                                                                                                                                                                                  |
| Web browser access ports:        | 80                                                                                                                                                                                                                                    |
| PC client access ports:          | Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application                                                                                                                                                                     |
| Mobile client access ports:      | 8000                                                                                                                                                                                                                                  |
| RTSP URL:                        | <ul style="list-style-type: none"><li>• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream</li><li>• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream</li></ul>  |
| Alarm inputs / outputs:          | 16 / 4                                                                                                                                                                                                                                |
| PTZ control:                     | <ul style="list-style-type: none"><li>• IP Speed Dome Cameras</li><li>• RS-485 - PELCO-D/P and others</li></ul>                                                                                                                       |
| Motion Detection:                | ✓                                                                                                                                                                                                                                     |
| Intelligent Image Analysis:      | ✓                                                                                                                                                                                                                                     |
| Mouse support:                   | ✓                                                                                                                                                                                                                                     |
| IR remote controller in the set: | —                                                                                                                                                                                                                                     |
| Switch PoE:                      | 16-port PoE Switch built-in, 25.5 W / Channel, PoE (802.3af/at)<br>max. 200 W (total)                                                                                                                                                 |
| Power supply:                    | 100 ... 240 V AC                                                                                                                                                                                                                      |
| Operation temp:                  | -10 °C ... 55 °C                                                                                                                                                                                                                      |
| Weight:                          | 4.6 kg                                                                                                                                                                                                                                |
| Dimensions:                      | 440 x 390 x 75 mm, RACK 19", 1.5U                                                                                                                                                                                                     |
| Supported languages:             | Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian |
| Country of origin:               | China                                                                                                                                                                                                                                 |
| Manufacturer / Brand:            | Hikvision                                                                                                                                                                                                                             |
| SAP Code:                        | 303602980                                                                                                                                                                                                                             |
| Guarantee:                       | <b>3 years</b>                                                                                                                                                                                                                        |