DATA SHEET

Code: S561D-G

VIDEO DOORPHONE **S561D-G** VIDOS



Video Doorphone is mounted in a flush-mounted housing. Surface mounting is possible with the D561B cover.
The S561D-G is designed to cooperation with video doorphones and panels working in analog VIDOS system.

Compatibility:	VIDOS Analog Video Doorphones
Sensor:	1/3 " 600 TVL
View angle:	87 °
IR illuminator:	✓
LED illuminator:	–
proximity reader built-in:	–
Fingerprint reader built-in:	–
Built-in keypad:	✓
The number of subscribers served:	1
Video output:	compatible with VIDOS analog video door-phone system
Main features:	• Adjustment of the opening time of the electric strike: 1s ... 99s • Electric strikes and electromagnetic locks support • Output for the additional lock release button • Timer output specifying temporary access • Vandal-proof front panel • Illuminated buttons and signboard for the surname

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

DATA SHEET

Power supply:	12 V DC ... 15 V DC
Power consumption:	≤ 1.5 W (operation)
Housing:	Acid-proof steel - powder painting / Plastic, Waterproof
Color:	Graphite
"Index of Protection":	IP65
Operation temp:	-20 °C ... 55 °C
Weight:	0.94 kg
Dimensions:	250 x 120 x 50 mm
Manufacturer / Brand:	VIDOS
Guarantee:	2 years

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60