

## DATA SHEET

Code: S1201A-SKP

## VIDEO DOORPHONE INTEGRATED WITH MAILBOX **S1201A-SKP** VIDOS

Video doorphone integrated with one-way mailbox. The box is designed for mounting in a fence post or wall. Thanks to the use of the highest quality materials, it is resistant to weather conditions.

The video doorphone has been equipped with a color camera with the possibility of adjusting horizontally and vertically in the range of several degrees.

The S1201A-SKP is dedicated for cooperation with video doorphones and panels

compatible with the VIDOS DUO digital system.



| Compatibility:                    | VIDOS DUO  |
|-----------------------------------|--|
| Sensor:                           | 1/2.7 " Fish Eye CMOS, 2 Mpx                                 |
| View angle:                       | 170 °  |
| IR illuminator:                   | 1  |
| LED illuminator:                  | <b>✓</b>   |
| proximity reader built-in:        | Standard : Unique EM 125kHz                                  |
| Built-in keypad:                  | -  |
| Fingerprint reader built-in:      | 1  |
| The number of subscribers served: | 1  |
| Video output:                     | compatible with the VIDOS DUO digital video doorphone system |

POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

S1201A-SKP 2024-04-27 1/2



## DATA SHEET

| Main features:         | Integrated mailbox - Through Wiring - 2 wires without polarity Relay output : 1 pcs or 2 pcs - B5 module Support up to 13 indoor devices (monitors / uniphones) PIR detectors support Permanent or cyclical zoom-up of the observed image Electric strikes and electromagnetic locks support Electric lock supply: 12V DC / max. 300mA Easy to add and delete users via MASTER key fobs |
|------------------------|---|
| Power supply:          | 24 V DC   |
| Power consumption:     | ≤ 3 W (operation)<br>≤ 0.8 W (Standby mode)   |
| Housing:               | Acid-proof steel, Waterproof  |
| Color:                 | Silver  |
| "Index of Protection": | IP65  |
| Operation temp:        | -20 °C 55 °C  |
| Weight:                | 4.78 kg   |
| Dimensions:            | • Front panel : 285 x 385 mm<br>• Rear panel : 265 x 360 mm<br>• Adjustable depth of the box : 190 255 mm   |
| Manufacturer / Brand:  | VIDOS   |
| Guarantee:             | 3 years   |