

Code: APTI-XB0802HS-4KS2

AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR **APTI-XB0802HS-4KS2** 8 CHANNELS 4K UHD

The APTI-XB0802HS-4KS2 digital recorder with AHD (Analog High Definition), HD-CVI (High Definition Composite Video Interface), HD-TVI (High Definition Transport Video Interface), TCP/IP and CVBS interface is a professional device applicable in surveillance systems.

The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.



Standard:	AHD, HD-CVI, HD-TVI, PAL, TCP/IP
Video inputs:	8 pcs BNC
Video outputs:	• 1 pcs HDMI • 1 pcs VGA • 1 pcs CVBS - BNC socket
Audio inputs:	6 pcs CINCH
Audio outputs:	1 pcs BNC
Image compression method:	H.265+ / H.265 / H.264+ / H.264



Image records resolutions:	• AHD : 8 Mpx - 3840 x 2160 px, 4K UHD , 5 Mpx - 2592 x 1944 px, 4 Mpx - 2560 x 1440 px, 3 Mpx - 2048 x 1536 px, 1080p - 1920 x 1080 px, 720p - 1280 x 720 px, • HD-CVI : 8 Mpx - 3840 x 2160 px, 4K UHD , 4 Mpx - 2560 x 1440 px, 1080p - 1920 x 1080 px, 720p - 1280 x 720 px, • HD-TVI : 8 Mpx - 3840 x 2160 px, 4K UHD , 5 Mpx - 2592 x 1944 px, 4 Mpx - 2560 x 1440 px, 3 Mpx - 2048 x 1536 px, 1080p - 1920 x 1080 px, 720p - 1280 x 720 px, • CVBS : 960H - 960 x 576 px, • IP : max. 8.3 Mpx - 3840 x 2160 px - 4K UHD
Recording speed adjustment:	8.3 Mpx IP @ 1 ... 25 fps 8.3 Mpx @ 1 ... 12 fps 5 Mpx @ 1 ... 20 fps 4 Mpx @ 1 ... 25 fps 3 Mpx @ 1 ... 18 fps 1080p @ 1 ... 25 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps for each channel
Operation modes:	• 8 x AHD / HD-CVI / HD-TVI / CVBS • 6 x AHD / HD-CVI / HD-TVI / CVBS + 10 x IP max. 8 Mpx • 4 x AHD / HD-CVI / HD-TVI / CVBS + 12 x IP max. 8 Mpx • 2 x AHD / HD-CVI / HD-TVI / CVBS + 14 x IP max. 8 Mpx • 17 x IP max. 8 Mpx • 26 x IP max. 5 Mpx • 32 x IP max. 4 Mpx All modes allow for any combination of the AHD, HD-CVI, HD-TVI, CVBS cameras
Recording modes:	Motion Detection, Schedule
Supported hard drives:	2 x 6 TB SATA
External storage devices backup:	Records backup at (.avi) format to USB (pendrive)
Searching and playback the records:	Records searching: timeline or file list. Playback: forward, backward, fast, slow. Records playback from max. 8 channels in the same time
Network functions:	• Network Client Software (iVMS320): live view, playback and backup of the records • IE browser: live view, playback and backup of the records and configuration of the recorder parameters
Mobile phones support:	Port no.: 6000 or access by a cloud (P2P) • Android: Free application BitVision, Android: Free application iVMS320 • iOS (iPhone): Free application BitVision, iOS: Free application iVMS320
Default IP address:	192.168.1.88
Default admin user / password:	admin / 12345



DATA SHEET

Web browser access ports:	80, 5000, 554
PC client access ports:	80, 5000, 554
Mobile client access ports:	80, 5000, 6000
Alarm inputs / outputs:	4 / 1
PTZ control:	Pelco-D, Pelco-P
Motion Detection:	Split the screen into zones : 22 x 18 motion zones
Mouse support:	✓
IR remote controller in the set:	—
Power supply:	12 V DC / 4 A (power adapter included)
Color:	Black
Weight:	1.48 kg
Dimensions:	310 x 306 x 47 mm
Supported languages:	Polish, English, Bulgarian, Czech, French, Greek, Spanish Dutch, German, Portuguese, Russian, Romanian, Turkish, Hungarian, Italian
Country of origin:	China
Manufacturer / Brand:	APTI
Guarantee:	2 years