

DATA SHEET

Code: DECO-M5(1-PACK)

WHOLE HOME WI-FI SYSTEM **DECO-M5(1-PACK)** 2.4 GHz, 5 GHz 400 Mbps + 867 Mbps TP-LINK

Deco is the easiest way to have a strong wireless signal in every corner of your house. The DECO-M5(1-PACK) provides fast and stable connection for all devices in houses with an area up to $500 \mathrm{m}^2$. The Deco system uses several devices to create a unified Wi-Fi network, and thanks to the advanced Mesh technology, devices are automatically switched when moving around the house.

The Deco Mx offers a stable connection with speeds up to $1.5\,$ Gb/s and is compatible with all cable modems, and the entire system can support up to $100\,$ wireless devices in the network. The system is configured using a very simple, free Deco application.



Number of devices included:	1 pcs
Frequency range:	2.4 GHz, 5 GHz
Antenna type:	4 x Omnidirectional antenna - embedded
Standards:	IEEE 802.11 b/g/n @ 2.4 GHz IEEE 802.11 a/n/ac @ 5 GHz
Baud rates:	400 Mbps + 867 Mbps
LAN ports:	2 x 10/100/1000 Mbps
LED indicators:	~
DDNS:	~
DHCP server:	~
Firmware update:	Automatic
Protections:	WEP 64/128-bit, WPA/WPA2, WPA-PSK/WPA2-PSK DoS attacks protection, SPI network firewall, domain filtering, IP and MAC filtering, IP and MAC binding



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



DATA SHEET

Management interface:	Web browser, TP-LINK Tether
Transmitter power:	max. 20 dBm @ 2.4 GHz max. 23 dBm @ 5 GHz
Power supply:	12 V DC / 1.2 A (power adapter included)
Main features:	The Deco Mx offers a stable connection with speeds up to 1.5 Gb/s and is compatible with all cable modems, and the entire system can support up to 100 wireless devices in the network TP-Link Mesh technology: MU-MIMO, Automatic route selection, AP control, Bandwidth control, Beamforming Port forwarding IPv4/IPv6 Guest Network - a separate and secure network for guests Black list Firewall WMM (Wi-Fi Multimedia) Internet access filtering Access control, parental control Remote management Static / dynamic routing Wireless transmission statistics
System requirements:	 Android 4.3 or newer iOS 8.0 or newer Bluetooth 4.0 or newer
Operation temp:	0 °C 40 °C
Permissible relative humidity:	10 % 90 % (non-condensing)
Weight:	0.22 kg
Dimensions:	Ø 120 x 37 mm
Manufacturer / Brand:	TP-LINK
Guarantee:	3 years