

Code: PFS6428-24T

## INDUSTRIAL SWITCH **PFS6428-24T** 24-PORT + 4 x SFP DAHUA

The PFS6428-24T switch is designed for large streams of video data in the CCTV IP surveillance networks. Designed to continuous operation 24/7.

The switch has been equipped with two independent power supply adapters. In case of failure of one of the power adapter, it is possible to immediately connect the other one and replace the damaged module.



LAN ports:	24 x RJ45 - 10/100/1000 Base-T
Transmission speed:	<ul style="list-style-type: none"> <li>• 10 / 100 / 1000 Mbps - 24 LAN ports,</li> <li>• 1 / 10 Gb/s - 4 SFP+ ports</li> </ul>
Management:	✓
MAC addresses table:	32k
Main features:	<ul style="list-style-type: none"> <li>• Switch is managed via a web browser, command line interface and SNMP, RMON protocols</li> <li>• Auto update of MAC addresses table</li> <li>• CoS/DSCP priority based on IEEE 802.1p standard</li> <li>• Queue scheduling: SP, WRR, SP+WRR</li> <li>• I/O stream rate management on port level</li> <li>• IEEE 802.1Q VLAN, Port Based VLAN, MAC Based VLAN, Private VLAN support</li> <li>• IEEE 802.1Q standard support, up to 512 VLAN groups and 4K VIDs</li> <li>• IGMP Snooping V1/V2/V3</li> <li>• Spanning Tree STP/RSTP/MSTP</li> <li>• BPDU Filtering/Guard</li> <li>• Data Flow Control (802.3x)</li> <li>• protection against lightning discharges and voltage differences and strokes between devices</li> <li>• The switch has been equipped with two independent power supply adapters - In case of failure of one of the power adapter, it is possible to immediately connect the other one and replace the damaged module</li> </ul>
Certificates:	CE, RoHS
Power supply:	230 V AC
Power consumption:	≤ 50 W
Operation temp:	0 °C ... 40 °C
Weight:	4.41 kg
Dimensions:	440 x 290 x 44 mm
Manufacturer / Brand:	DAHUA



# DATA SHEET

Guarantee:

**3 years**