

Code: PFS5424-24T

## SWITCH **PFS5424-24T** 24-PORT SFP DAHUA

The PFS5424-24T Switch is an industrial type device enabling fluent network transmission at rates 10 / 100 / 1000 Mbps.

Attention! The SFP port requires the SFP module, which is available in our offer.



|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LAN ports:            | <ul style="list-style-type: none"> <li>• 20 x RJ45,</li> <li>• 4 x port Combo: SFP (Base-X) / RJ45 (Base-T) - Uplink</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                               |
| Transmission speed:   | <ul style="list-style-type: none"> <li>• 10 / 100 / 1000 Mbps - 20 LAN ports,</li> <li>• 1000 Mbps - 4 SFP ports / Uplink ports</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                    |
| MAC addresses table:  | 32k                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Management:           | ✓                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Main features:        | <ul style="list-style-type: none"> <li>• Switch is managed via a web browser, command line interface and SNMP, RMON protocols</li> <li>• Port/flow-based rate limiting</li> <li>• IEEE 802.1Q VLAN, Port Based VLAN, MAC Based VLAN, Private VLAN support</li> <li>• IEEE 802.1Q standard support, up to 512 VLAN groups and 4K VIDs</li> <li>• IGMP Snooping V1/V2/V3</li> <li>• Spanning Tree STP/RSTP/MSTP</li> <li>• BPDU Filtering/Guard</li> <li>• Loop back detection</li> <li>• Data Flow Control (802.3x)</li> </ul> |
| LED diodes:           | Power, Link/Act, System                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Certificates:         | CE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Power supply:         | 100 ... 240 V AC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Weight:               | 3.84 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Dimensions:           | 440 x 285 x 44 mm, RACK 19", 1U                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Manufacturer / Brand: | DAHUA                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Guarantee:            | 2 years                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |