

Code: IPC-HFW1431S-0360B

## IP CAMERA **IPC-HFW1431S-0360B** 4 Mpx 3.6 mm DAHUA

IP camera with efficient H.265 / H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of 4 MPx.

The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.



|                           |                                                                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standard:                 | TCP/IP                                                                                                                                                                 |
| Sensor:                   | 1/3 " Progressive Scan CMOS                                                                                                                                            |
| Matrix size:              | 4 Mpx                                                                                                                                                                  |
| Scanning system:          | Progressive                                                                                                                                                            |
| Resolution:               | 2688 x 1520 - 4 Mpx ,<br>2560 x 1440 - 3.6 Mpx ,<br>2304 x 1296 - 3 Mpx ,<br>1920 x 1080 - 1080p<br>1280 x 1024 - 1.4 Mpx<br>1280 x 960 - 1.3 Mpx<br>1280 x 720 - 720p |
| Lens:                     | 3.6 mm                                                                                                                                                                 |
| View angle:               | • 83 ° (manufacturer data)<br>• 80 ° (our tests result)                                                                                                                |
| Range of IR illumination: | 30 m                                                                                                                                                                   |
| S/N ratio:                | > 50 dB                                                                                                                                                                |
| RS-485 interface:         | —                                                                                                                                                                      |
| Memory card slot:         | —                                                                                                                                                                      |
| Image compression method: | H.265 / H.264 / MJPEG                                                                                                                                                  |
| Alarm inputs / outputs:   | —                                                                                                                                                                      |



# DATA SHEET

|                                |                                                                                                                                                                                                                                                                                                                                                                               |
|--------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Audio:                         | —                                                                                                                                                                                                                                                                                                                                                                             |
| Bitrate:                       | 5 ... 10240 kbps - H.264                                                                                                                                                                                                                                                                                                                                                      |
| Main stream frame rate:        | 20 fps @ 4.0 Mpx<br>25 fps @ 3.6 Mpx                                                                                                                                                                                                                                                                                                                                          |
| Network interface:             | 10/100 Base-T (RJ-45)                                                                                                                                                                                                                                                                                                                                                         |
| Network protocols:             | HTTP, HTTPS, IPv4/IPv6, TCP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, UPnP, NTP, QoS, Bonjour, IEEE 802.1x, Multicast, ICMP, IGMP, SNMP                                                                                                                                                                                                                             |
| WEB Server:                    | Built-in                                                                                                                                                                                                                                                                                                                                                                      |
| Max. number of on-line users:  | 20                                                                                                                                                                                                                                                                                                                                                                            |
| ONVIF:                         | 16.12                                                                                                                                                                                                                                                                                                                                                                         |
| Mobile phones support:         | Port no.: 37777 or access by a cloud (P2P)<br>• Android: Free application <a href="#">DMSS</a><br>• iOS (iPhone): Free application <a href="#">DMSS</a>                                                                                                                                                                                                                       |
| Default admin user / password: | admin / -<br>The administrator password should be set at the first start                                                                                                                                                                                                                                                                                                      |
| Default IP address:            | 192.168.1.108                                                                                                                                                                                                                                                                                                                                                                 |
| Web browser access ports:      | 80, 37777                                                                                                                                                                                                                                                                                                                                                                     |
| PC client access ports:        | 37777                                                                                                                                                                                                                                                                                                                                                                         |
| Mobile client access ports:    | 37777                                                                                                                                                                                                                                                                                                                                                                         |
| Port ONVIF:                    | 80                                                                                                                                                                                                                                                                                                                                                                            |
| RTSP URL:                      | rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream<br>rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream                                                                                                                                                                                               |
| Main features:                 | <ul style="list-style-type: none"><li>• 3D-DNR - Digital Noise Reduction</li><li>• D-WDR - Wide Dynamic Range</li><li>• BLC/HLC - Back Light / High Light Compensation</li><li>• Possibility to change the resolution, quality and bit rate</li><li>• Motion Detection</li><li>• Privacy zones</li><li>• Configurable Privacy Zones</li><li>• Mirror - Mirror image</li></ul> |
| Power supply:                  | <ul style="list-style-type: none"><li>• PoE (802.3af),</li><li>• 12 V DC / 470 mA</li></ul>                                                                                                                                                                                                                                                                                   |
| Power consumption:             | ≤ 5.7 W                                                                                                                                                                                                                                                                                                                                                                       |
| Housing:                       | Compact - Aluminum                                                                                                                                                                                                                                                                                                                                                            |
| Color:                         | White                                                                                                                                                                                                                                                                                                                                                                         |
| "Index of Protection":         | IP67                                                                                                                                                                                                                                                                                                                                                                          |
| Operation temp:                | -30 °C ... 60 °C                                                                                                                                                                                                                                                                                                                                                              |
| Weight:                        | 0.4 kg                                                                                                                                                                                                                                                                                                                                                                        |
| Dimensions:                    | Ø 70 x 165 mm                                                                                                                                                                                                                                                                                                                                                                 |
| Supported languages:           | English, Polish                                                                                                                                                                                                                                                                                                                                                               |



# DATA SHEET

---

|                       |         |
|-----------------------|---------|
| Manufacturer / Brand: | DAHUA   |
| Guarantee:            | 3 years |