

Code: IPC-HDBW1235E-W-0360B

## IP VANDALPROOF CAMERA **IPC-HDBW1235E-W-0360B** Wi-Fi - 1080p 3.6 mm DAHUA

IP camera with efficient H.264 / H.265 image compression algorithm for clear and smooth video streaming at maximal resolution of 1920 x 1080 (1080p).

The used Wi-Fi module allows to remote communication with camera for max. distance up to 50 m.

The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance). Camera is according to IP67 Index of Protection norm.

In order to obtain optimal performance of DAHUA Wi-Fi series cameras, it is recommended to use DAHUA Micro SD memory cards.



|                           |                                                                      |
|---------------------------|----------------------------------------------------------------------|
| Standard:                 | TCP/IP                                                               |
| Sensor:                   | 1/2.9 " Progressive Scan CMOS                                        |
| Matrix size:              | 2.1 Mpx                                                              |
| Scanning system:          | Progressive                                                          |
| Resolution:               | 1920 x 1080 - 1080p                                                  |
| Lens:                     | 3.6 mm                                                               |
| View angle:               | 83 °                                                                 |
| Range of IR illumination: | 30 m                                                                 |
| Memory card slot:         | Micro SD memory cards up to 128GB support (possible local recording) |
| Image compression method: | H.265                                                                |
| Alarm inputs / outputs:   | —                                                                    |
| Audio:                    | —                                                                    |
| Bitrate:                  | 32 ... 10240 kbps - H.264                                            |
| Network interface:        | 10/100 Base-T (RJ-45), Wi-Fi IEEE 802.11 b/g/n                       |
| Network protocols:        | TCP, DHCP                                                            |
| WEB Server:               | Built-in, NVR compliance                                             |
| ONVIF:                    | ✓                                                                    |

|                                |                                                                                                                                                                                              |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Main features:                 | <ul style="list-style-type: none"> <li>• Wi-Fi module - IEEE 802.11 b/g/n, Range : 50 m (open area) ; Antenna - SMA socket</li> <li>• Motion Detection</li> </ul>                            |
| Mobile phones support:         | Access by a cloud (P2P)<br><ul style="list-style-type: none"> <li>• Android: Free application <a href="#">DMSS</a></li> <li>• iOS (iPhone): Free application <a href="#">DMSS</a></li> </ul> |
| Default admin user / password: | admin / -<br>The administrator password should be set at the first start                                                                                                                     |
| Default IP address:            | DHCP                                                                                                                                                                                         |
| Web browser access ports:      | 80, 37777                                                                                                                                                                                    |
| PC client access ports:        | 37777                                                                                                                                                                                        |
| Mobile client access ports:    | 37777                                                                                                                                                                                        |
| Port ONVIF:                    | 80                                                                                                                                                                                           |
| RTSP URL:                      | rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream<br>rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream              |
| Power supply:                  | 12 V DC / 540 mA                                                                                                                                                                             |
| Power consumption:             | < 6.5 W                                                                                                                                                                                      |
| Housing:                       | Dome - Metal                                                                                                                                                                                 |
| Color:                         | White                                                                                                                                                                                        |
| Vandal-proof:                  | IK10                                                                                                                                                                                         |
| "Index of Protection":         | IP67                                                                                                                                                                                         |
| Operation temp:                | -10 °C ... 50 °C                                                                                                                                                                             |
| Weight:                        | 0.400 kg                                                                                                                                                                                     |
| Dimensions:                    | Ø 110 x 81 mm                                                                                                                                                                                |
| Supported languages:           | Polish, English                                                                                                                                                                              |
| Manufacturer / Brand:          | DAHUA                                                                                                                                                                                        |
| Guarantee:                     | <b>3 years</b>                                                                                                                                                                               |