

Code: HAC-LC1200T-TH-0280B

## AHD, HD-CVI, HD-TVI, PAL CAMERA **HAC-LC1200T-TH-0280B** - 1080p 2.8 mm DAHUA

Megapixel camera with 1/2.7" CMOS sensor and AHD / HD-CVI / HD-TVI / PAL.

The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in max. 8 Mpx (4K UHD) resolution. During transmission there are no delays and is maintained the original, high quality image.

In the case of video transmission using a twisted pair cable and matching transformers (balun), be aware of the possibility of signal reflections and interfering signals.

Attention! The camera default setting is HD-CVI standard. To change the camera standard you need use the PFM820 controller, available separately.

Camera is according to IP67 Index of Protection norm. The 3-Axis integrated camera bracket has a regulation in all three planes, which allows to turn the camera to any direction.

In addition to the standard functions, the device has also been adapted to work with advanced monitoring systems of the DAHUA brand that meet the objectives of the Internet of Things concept (IoT). The camera has a built-in thermometer and hygrometer. Readings from the sensors are sent together with the HD-CVI signal to the recorder via a coaxial cable. In addition, it is possible to display the reading from the sensors in the camera image (as OSD image). The recorder has the option of displaying the collected data in real time on the screen, putting them on the camera image, displaying the statistics, and also programming the alarm states in the case of eg opening the door, smoke detection or a rapid temperature increase.

**Attention!** The IoT functions work only with the recorders of the DHI-XVR7xxx-4KL series.



|                                  |   |
|----------------------------------|---|
| Standard:                        | AHD, HD-CVI, HD-TVI, PAL  |
| Sensor:                          | 1/2.9 " Progressive Scan CMOS   |
| Matrix size:                     | 2.1 Mpx   |
| Resolution:                      | 1920 x 1080 - 1080p - AHD, HD-CVI, HD-TVI<br>960 x 576 - 960H PAL   |
| Lens:                            | 2.8 mm  |
| View angle:                      | <ul style="list-style-type: none"> <li>• 104 ° (manufacturer data)</li> <li>• 101 ° (our tests result)</li> </ul> |
| Range of IR illumination:        | 20 m  |
| IR illuminator power adjustment: | Automatic   |
| Video output:                    | AHD / HD-CVI / HD-TVI / PAL, 1 Vpp / 75 Ω   |
| S/N ratio:                       | > 65 dB   |
| OSD menu:                        | ✓   |

|                        |   |
|------------------------|---|
| Main features:         | <ul style="list-style-type: none"> <li>• Thermometer built-in</li> <li>• Built-in hygrometer</li> <li>• Displaying the reading from the sensors in the camera image (as OSD image)</li> <li>• Cooperation with Dahua devices working in the concept of the Internet of Things (IoT)</li> <li>• D-WDR - Wide Dynamic Range</li> <li>• 2D-DNR - Digital Noise Reduction</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• ICR - Movable InfraRed filter</li> <li>• Sharpness - sharper image outlines</li> <li>• AGC - Automatic Gain Control</li> <li>• Privacy zones</li> <li>• Mirror - Mirror image</li> <li>• Auto White Balance</li> </ul> |
| Power supply:          | 12 V DC / 280 mA  |
| Power consumption:     | ≤ 3.4 W   |
| Housing:               | Compact, Metal  |
| Color:                 | White   |
| "Index of Protection": | IP67  |
| Operation temp:        | -40 °C ... 60 °C  |
| Weight:                | 0.4 kg  |
| Dimensions:            | 176 x 85 x 75 mm  |
| Manufacturer / Brand:  | DAHUA   |
| Guarantee:             | <b>3 years</b>  |