

Code: PFM880

ACCESS POINT WITH ANTENNA **PFM880** DAHUA



The PFM880 is an integrated solution for professional outdoor wireless networks. Thanks to a unique construction, device offers unparalleled performance in such a compact device.
The casing made of UV resistant plastic is resistant to even the most severe weather conditions.

Frequency range:	5470 MHz ... 5825 MHz
Antenna type:	16 dBi Outdoor, 2Tx 2Rx MIMO
Polarization:	vertical/horizontal
Standards:	802.11 a/n
Baud rates:	max. 300 Mbps
Wireless transmission range:	max. 3 km
Max. power consumption:	10 W
Ethernet interface:	1 x 10/100 Mbps BASE-TX (Cat. 5, RJ-45)
Vertical beam width (V):	12 °
Horizontal beam width (H):	90 °
Operation mode:	Client, WDS client, Access Point, Access Point WDS, Repeater
Protections:	15kV surge protection of radio line
Transmitter power:	27 dBm

Receiver sensitivity:	• -74 dBm @ 65 Mbps • -96 dBm @ 1 Mbps
Processor:	Atheros AR7240, 400 MHz
Port USB:	—
Power supply PoE:	✓
Power supply:	24 V / 0.5 A PoE (power adapter included)
Operation temp. / Relative humidity:	-30 °C ... 70 °C / 5 % ... 95 %
Weight:	2.10 kg - device 0.82 kg - Antenna
Dimensions:	290 x 265 x 66 mm - device 450 x 140 x 55 mm - Antenna
Manufacturer / Brand:	DAHUA
Guarantee:	3 years