

## DATA SHEET

Code: ASP-200-R

## WIRELESS OUTDOOR SIREN ASP-200-R ABAX/ABAX2 SATEL

Outdoor, wirelessly triggered opto-acoustic siren designed to use in burglary and robbery signaling systems. Optical signaling source are LEDs, and acoustical signaling is generating by piezo transducer.

The device powered by the BAT-ER-3,6 powerful battery with a capacity of  $13~\mathrm{Ah}$  and a high temperature range.

High-impact polycarbonate enclosure, featuring a very high mechanical strength and guarantees aesthetic appearance of siren even after many years of using. Construction enables high level of tamper protection (against opening and removing from mounting surface).

The ASP-200-R supports the other devices copmpatible with wireless ABAX/ABAX2 system.

Attention! The device does not work with the ACU-100, ACU-250, ARU-100, INTEGRA-128-WRL.



Support:	ABAX/ABAX2
Sound pressure level:	105 dB
Frequency bandwidth of the system:	868.0 MHz 868.6 MHz
Radio communication range (at open area):	max. 500 m @ ABAX , max. 2000 m @ ABAX2
Main features:	Optical and acoustic signaling is triggered independently, by radio Tamper protection (detection of removing from mounting surface and enclosure opening) Remote configuration Selection of 4 different acoustic signals The advanced radio system ensures optimized communication with low current consumption Remote configuration Remote update of module software battery diagnostics Light and durable construction
Color:	Red
Power supply:	Battery BAT-ER-3,6 (ER34615) 13 Ah (included)
Maximal current consumption:	480 mA



## DATA SHEET

Backup time:	2 years
Operation temp:	-40 °C 55 °C
Weight:	0.8 kg
Dimensions:	148 x 254 x 64 mm
Manufacturer / Brand:	SATEL
Guarantee:	2 years