

Code: PFWB2-60N

CUSTOMER PREMISES EQUIPMENT **PFWB2-60N** DAHUA

The PFWB2-60N is an integrated solution for professional outdoor wireless networks. Thanks to a unique construction, device offers unparalleled performance in such a compact device.

The casing made of UV resistant plastic is resistant to even the most severe weather conditions.



Frequency range:	2402 MHz ... 2492 MHz
Antenna type:	9 dBi, 2x2 MIMO - Bandwidth 2.4 GHz
Standards:	IEEE 802.11 b/g/n
Baud rates:	max. 300 Mbps
LAN ports:	1 x 10/100 Mbps
Vertical beam width (V):	60 °
Horizontal beam width (H):	60 °
Operation modes:	WDS client, TDMA client, WDS Base Station, TDMA Base Station, ARP NAT Base Station, Bridge, Router
Protections:	Overvoltage protection
Transmitter power:	31 dBm
Wireless transmission range:	- Recommended ≤ 3 km - max. 5 km
Power supply PoE:	✓
Power supply:	12 V ... 24 V DC - Passive PoE (power adapter included)



DATA SHEET

Power consumption:	4.5 W
Operation temp:	-30 °C ... 70 °C
Weight:	0.31 kg
Dimensions:	154 x 116 x 58 mm
Manufacturer / Brand:	DAHUA
Guarantee:	2 years