DATA SHEET

Code: S1001

VIDEO DOORPHONE **S1001** VIDOS



Video Doorphone is mounted in a surface housing. The S1001 is dedicated for cooperation with video doorphones and panels compatible with the VIDOS DUO digital system.

Compatibility:	VIDOS DUO
Sensor:	1/2.7 ", 600 TVL
View angle:	105 °
IR illuminator:	–
LED illuminator:	✔
proximity reader built-in:	–
The number of subscribers served:	1
Video output:	compatible with the VIDOS DUO digital video doorphone system
Main features:	• Wiring - 2 wires without polarity • Relay output : 1 pcs or 2 pcs - B5 module • Support up to 13 indoor devices (monitors / uniphones) • Provides the function of an addressed intercom - it allows the addressing of internal panels in the system and communication between them • PIR detectors support • Electric strikes and electromagnetic locks support • Electric lock supply: 12V DC / max. 300mA • Call start and lock opening indicator

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

DATA SHEET

Power supply:	24 V DC
Power consumption:	≤ 3 W (operation) ≤ 0.3 W (Standby mode)
Housing:	Aluminum, Waterproof
Color:	Silver
"Index of Protection":	IP54
Operation temp:	-20 °C ... 55 °C
Weight:	0.28 kg
Dimensions:	160 x 60 x 32 mm
Manufacturer / Brand:	VIDOS
Guarantee:	**3 years**

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60