

DATA SHEET

Code: DS-KH8340-TCE2

INDOOR PANEL DS-KH8340-TCE2 Hikvision



The DS-KH8340-TCE2 panel has been designed to create a simple and effective system of local communication. It can be also used as simple alarm control panel, or notification module by the support 8 alarm inputs.

The device is fully configurable via the **iVMS4200** software. In addition, the device has the ability to work with the **Hik-Connect** application on mobile devices.

Compatibility:	Interphone installation - HIKVISION 2-wire
Shield:	7 " - capacitive touch screen
Resolution:	1024 x 600
Internal memory:	-
Memory card slot:	SD memory cards up to 32GB support (possible local recording)
Mobile phones support:	Android: Free application Hik-Connect iOS (iPhone): Free application Hik-Connect
Default administrator password:	888999
Main features:	Microphone built-in, Speakers built-in, Bidirectional communication, Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, Automatically capture and save photos if there is no response to the bell button, Support for capturing a photo during video calls, Register a short voice message if there is no response to the bell button, Full support via network, LEDs for system state indication and user interface display, Possibility to connect up to 3 compatible devices (door stations, internal panels, KAD-709 controller), Support for capturing a photo during video calls, IP Hikvision cameras support



DATA SHEET

Controlling:	One-touch action buttons + capacitive touch screen
Alarm inputs:	-
Power supply:	24 V DC - via DS-KAD709
Power consumption:	≤ 10 W
Color:	Black
Operation temp:	-10 °C 50 °C
Weight:	0.52 kg
Dimensions:	196 x 133 x 25 mm
Supported languages:	Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Romanian, Serbian, Hungarian, Italian
Manufacturer / Brand:	Hikvision
SAP Code:	305301219
Guarantee:	3 years