

## DATA SHEET

## Code: IP-9-11-L2 SWITCH POE **IP-9-11-L2** 8-PORT ATTE



The IP-9-11-L2 set consists of 2 XPOE-6-11-OF modules and the APS-90-480-OF switching power supply enclosed in the ABOX-L2 external enclosure with IP56 tightness class.

The LONG RANGE operation mode allows to increase the range of power and data transmission for ports LAN 1 ... LAN 4 to 280m while limiting the network bandwidth for these ports to 10Mbps. It is possible to use the LONG RANGE mode independently in each of the XPOE-6-11-OF modules.

LAN ports:	<ul> <li>1 x RJ45 10/100 Base-T - Uplink</li> <li>9 x RJ45 10/100 Base-T + PoE (802.3af/at) / Passive PoE</li> </ul>
Management:	-
LED diodes:	Power, LAN
Transmission speed:	10 / 100 Mbps : 1 Port LAN + 9 LAN & PoE ports
Maximal output power:	<ul> <li>40 W @ Passive PoE - 1 4 ports,</li> <li>70 W @ Passive PoE - Port 5,</li> <li>30 W @ PoE (802.3af/at) - 1 5 ports</li> </ul>
Maximal total power:	96 W
Operation modes:	<ul> <li>Normal : 100 m @ 10/100 Mb/s - 1 5 ports</li> <li>Long Range : 280 m @ 10 Mb/s - 1 4 ports ; 100 m @ 10/100 Mb/s - Port 5</li> </ul>





## DATA SHEET

Main features:	<ul> <li>Possible cascading device connection (power transmission between devices using Passive PoE via LAN 5 port)</li> <li>The LAN 5 (PoE IN/OUT) port can be used to power PoE devices as well as to draw power from other devices</li> <li>The output PoE voltage is equal to the input voltage</li> <li>The ability to independently turn on and off the PoE power for each of the LAN 1 LAN 5 ports</li> <li>The modular design streamlines service tasks and enables quick and easy system expansion</li> <li>The raster system of module assembly facilitates the expansion of the device by further modules</li> <li>The ABOX-L2 mounting enclosure is equipped with 11 cable entries with glands in the 10 x M16 + 1 x M20 arrangement</li> </ul>
Power supply:	230 V AC - cable terminals
Weight:	1.05 kg
Dimensions:	248 x 222 x 96 mm
Manufacturer / Brand:	ATTE
Guarantee:	3 years

