

## DATA SHEET

## Code: ATE-D04SD-T2 AHD MOBILE DVR **ATE-D04SD-T2** 4 CHANNELS AUTONE

The ATE-D04SD-T2 is a mobile recorder designed to use in coaches, city buses, busses, trams, subway, corporate and personal vehicles and special vehicles ie. lorries, police cars, prison or military cars, ambulances. The device has been specially designed so that exhibited increased resistance to oscillations and vibrations. Recorder supports 2 SD cards with capacity up to 256 GB each.

The power cables of the ATE-D04SD-T2 are connected to the car's battery and ignition (analogous to radio receiver), so when you turn the ignition device automatically begins recording the audio-video data.



| Standard:                            | AHD   |
|--------------------------------------|---|
| Video inputs:                        | 4 pcs M12, 4-pin plug, Code A   |
| Video outputs:                       | 1 pcs CINCH - CVBS ,<br>1 pcs VGA ,<br>1 pcs HDMI                     |
| Audio inputs:                        | 4 pcs - Audio from cameras  |
| Audio outputs:                       | 1 pcs CINCH   |
| Resolution of recording video files: | 1920 x 1080 @ 25 fps ,<br>1280 x 720 @ 25 fps ,<br>720 x 576 @ 25 fps |
| Max. capacity of memory card:        | 2 x 256 GB SD/SDHC  |
| Supported hard drives:               | -   |
| Image compression method:            | H.264   |
| Number of compression levels:        | 7   |
| GPS:                                 | -   |
| Wi-Fi:                               | -   |
| 3G/4G:                               | -   |
| SIM socket:                          | -   |
| G-Sensor:                            | ¥   |
| RS-485:                              | ¥   |
| RS-232:                              | -   |



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



## DATA SHEET

| Alarm inputs / outputs: | 4 / 1   |
|-------------------------|---|
| Power supply:           | 8 V 36 V DC   |
| Main features:          | <ul> <li>Powering the cameras with 12V DC voltage directly from recorder</li> <li>Auto recording after power on</li> <li>Firmware upgrade via USB port</li> </ul> |
| Operation temp:         | -20 °C 70 °C  |
| Weight:                 | 0.52 kg   |
| Dimensions:             | 174 x 147 x 41 mm   |
| Manufacturer / Brand:   | AUTONE  |
| Guarantee:              | 2 years   |

