

DATA SHEET

Code: DS-PD2-D12-W WIRELESS DUAL TECHNOLOGY MICROWAVE + PIR DETECTOR **DS-PD2-D12-W** Hikvision



Wireless motion detector, which is designed to detect the moving intruder within the system protected area. With a combination of PIR and MW detection was reached high immunity to false alarms. It is perfect to create surveillance system in small-size buildings, such as e.g.: kiosks, summer houses, boutiques, freestanding garages and workshops, and wherever conducting wire installation is difficult or impossible to perform.

The DS-PD2-D12-W supports the other devices copmpatible with wireless Pyronix system.

Support:	Wireless alarm systems HIKVISION AX / PYRONIX Enforcer
Frequency band:	868 MHz
Radio communication range (at open area):	max. 800 m
PIR detection range:	12 m / 85 °
Microwave frequency band:	10.515 MHz
Power supply:	2 x 3 V Battery type : CR123A
Battery working time (in energy saving mode):	~ 2 years
Target speed range:	0.3 3 m/s
Digital temperature compensation:	¥
Pet immunity:	-
Recommended installation height:	1.8 2.4 m



DS-PD2-D12-W



DATA SHEET

Main features:	 Passive Infra Red (PIR) and microwave (MW) PIR / MW detection sensitivity adjustment Quick pairing of the detector with the alarm control panel using a single button With a combination of PIR and MW detection was reached high immunity to false alarms Tamper detection - opening the enclosure, removing from mounting surface
Operation temp:	-10 °C 40 °C
Color:	White
Dimensions:	117 x 69 x 59 mm
Weight:	0.161 kg
Manufacturer / Brand:	Hikvision
SAP Code:	302401119
Guarantee:	2 years



DS-PD2-D12-W