

Code: VTO2202F-P

VIDEO DOORPHONE **VTO2202F-P** DAHUA

Attention! When selecting 2-wire devices, check the compatibility list available at the bottom of the page in the "files" section.



Sensor:	2 Mpx CMOS
Lens:	1.95 mm
View angle:	160 °
proximity reader built-in:	—
Image compression method:	H.264
LED illuminator:	—
IR illuminator:	✓
Compatibility:	DAHUA
RS-485:	✓
Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS

Main features:	• Micro SD memory cards up to 64GB support (possible local recording), • Doorbell button, • LED diodes, • Monitoring the status of individual doors, • D-WDR - Wide Dynamic Range, • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Tamper detection - removing from mounting surface, • Power output 12 V DC / 100 mA
Power supply:	• PoE (802.3af), • 12 V DC, • 2-Wire IP interface
Power consumption:	≤ 12 W
Housing:	Aluminum
Color:	Silver
"Index of Protection":	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone
IK rating:	IK07
Operation temp:	-30 °C ... 60 °C
Weight:	0.32 kg
Dimensions:	130 x 96 x 28.5 mm
Supported languages:	Polish, English, Bulgarian, Czech, Finnish, Slovenian, Slovak, Hungarian
Manufacturer / Brand:	DAHUA
Guarantee:	3 years