

Code: UT-20B

UNIVERSAL METER **UT-20B** UNI-T

UT-20B is a universal digital meter used to measure: voltage, current, resistance. The device also has a built-in battery tester.



DC voltage measurement:	200 mV $\pm$ (1.5% + 2) @ 0.1 mV , 2000 mV $\pm$ (2.5% + 2) @ 1 mV , 20 V $\pm$ (2.5% + 2) @ 10 mV , 200 V $\pm$ (2.5% + 2) @ 100 mV , 300 V $\pm$ (2.5% + 2) @ 1 V
AC voltage measurement:	200 V $\pm$ (2.5% + 15) @ 100 mV , 300 V $\pm$ (2.5% + 15) @ 1 V
DC current measurement:	2000 μ A $\pm$ (2.5% + 10) @ 1 μ A , 20 mA $\pm$ (2.5% + 10) @ 10 μ A , 200 mA $\pm$ (2.5% + 10) @ 100 μ A
AC current measurement:	—
Resistance measurement:	200 Ω $\pm$ (2.5% + 5) @ 0.1 Ω , 2000 Ω $\pm$ (2.5% + 5) @ 1 Ω , 20 k Ω $\pm$ (2.5% + 5) @ 10 Ω , 200 k Ω $\pm$ (2.5% + 5) @ 100 Ω , 2000 k Ω $\pm$ (2.5% + 5) @ 1 k Ω
Capacitance measurement:	—
Inductance measurement:	—
Frequency measurement:	—
Temperature measurement:	—
Automatic change of measuring ranges:	—
hFE:	—
Diode test:	✓
Sound signal of the continuity test:	—

Checking TTL logic states:	—
RS-232:	—
Main features:	• Measurement of the battery discharge level: 9V, 1.5V, • Large, readable LCD display, • Low battery indicator, • Aesthetic and solid construction, • Built-in rectangular signal source with a frequency of 50 Hz and an output resistance of 47 kΩ
Power supply:	12V, type A23 battery - included
Weight:	0.08 kg
Dimensions:	94 x 55 x 29 mm
Manufacturer / Brand:	UNI-T
Guarantee:	2 years