

Code: NVR208S-P8

## NVR **NVR208S-P8** 8 CHANNELS, 8 PoE UNIARCH

The UNIARCH series product has been designed to minimize costs while maintaining high quality and ease of use.



|                                     |                                                                                                                                                                                        |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standard:                           | TCP/IP                                                                                                                                                                                 |
| Supported resolutions:              | max. 8 Mpx - 3840 x 2160 px, 4K UHD                                                                                                                                                    |
| Video outputs:                      | 1 pcs HDMI 4K<br>1 pcs VGA                                                                                                                                                             |
| Audio support:                      | 8 Channels - Audio from cameras                                                                                                                                                        |
| Audio inputs:                       | 1 pcs Cinch socket                                                                                                                                                                     |
| Audio outputs:                      | 1 pcs Cinch socket                                                                                                                                                                     |
| Image compression method:           | Ultra 265 / H.265 / H.264                                                                                                                                                              |
| Supported hard drives:              | 2 x 10 TB SATA                                                                                                                                                                         |
| Recording modes:                    | Manual, Motion Detection, Schedule                                                                                                                                                     |
| Network protocols:                  | P2P, UPnP, NTP, DHCP, PPPoE, ONVIF                                                                                                                                                     |
| External storage devices backup:    | Backup to USB drive (pendrive, external drive)                                                                                                                                         |
| Searching and playback the records: | Records searching: by time and events type. Records playback: forward, backward, fast, slow<br>Advanced searching (to the one second accuracy)<br>Synchronous playback of all channels |
| Network functions:                  | Full support via network, Remote records copying, Web Server built-in<br>max. 128 on-line users                                                                                        |
| Bitrate:                            | max. 160 Mbps                                                                                                                                                                          |
| Default admin user / password:      | admin / 123456                                                                                                                                                                         |
| Default IP address:                 | DHCP or 192.168.1.30                                                                                                                                                                   |
| RTSP URL:                           | rtsp://192.168.1.30:554/unicast/c1/s0/live - Main stream<br>rtsp://192.168.1.30:554/unicast/c1/s1/live - Sub stream                                                                    |



# DATA SHEET

|                                  |                                                                                                                                                                                                              |
|----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Web browser access ports:        | 80, 554                                                                                                                                                                                                      |
| PC client access ports:          | Port no.: 80 or access by a cloud (P2P) - PC: Free application <a href="#">Uniarch Client</a>                                                                                                                |
| Mobile client access ports:      | 80                                                                                                                                                                                                           |
| Mobile phones support:           | Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none"><li>• Android: Free application <a href="#">Uniarch</a></li><li>• iOS (iPhone): Free application <a href="#">Uniarch</a></li></ul> |
| Alarm inputs / outputs:          | 4 / 1                                                                                                                                                                                                        |
| PTZ control:                     | IP Speed Dome Cameras                                                                                                                                                                                        |
| Motion Detection:                | ✓                                                                                                                                                                                                            |
| USB:                             | 2 x USB 2.0                                                                                                                                                                                                  |
| Mouse support:                   | ✓                                                                                                                                                                                                            |
| IR remote controller in the set: | —                                                                                                                                                                                                            |
| Switch PoE:                      | 8-port PoE Switch built-in, 30 W / Channel, PoE (802.3af/at)                                                                                                                                                 |
| Maximum total switch load:       | 130 W                                                                                                                                                                                                        |
| Power supply:                    | 230 V AC                                                                                                                                                                                                     |
| Weight:                          | 2.4 kg                                                                                                                                                                                                       |
| Dimensions:                      | 380 x 324 x 53 mm                                                                                                                                                                                            |
| Supported languages:             | Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovak, Italian                                                                                                                          |
| Country of origin:               | China                                                                                                                                                                                                        |
| Manufacturer / Brand:            | UNIVIEW / UNIARCH                                                                                                                                                                                            |
| Guarantee:                       | <b>3 years</b>                                                                                                                                                                                               |