

## DATA SHEET

## Code: SPL-2010-R OUTDOOR SIREN **SPL-2010-R** SATEL

The SPL-2010-R optical-acoustic outdoor siren performs the signaling function in two ways: red optical signaling (by means of blinking LEDs) and acoustical signaling (by means of modulated high-volume sound signal).

The device is equipped with 2 control inputs - possibility to select the control method. Construction enables high level of tamper protection (against opening and removing from mounting surface).

Internal shield made of galvanized plate ensure an additional protection of electronics against mechanical damage. High-impact polycarbonate enclosure, featuring a very high mechanical strength and guarantees aesthetic appearance of siren even after many years of using.

Contraction of the second s		
a second s		
the second se		
<ul> <li>A second sec second second sec</li></ul>		
and the second se		
		-
		and the second
		Contraction of the second s
and the second		
		and the second
		and the second
A REAL PROPERTY AND A REAL	and the second se	
	and the second se	

Sound pressure level:	120 dB
Main features:	<ul> <li>Tamper protection (detection of removing from mounting surface and enclosure opening)</li> <li>Tamper protection against foaming</li> </ul>
Maximal current consumption:	550 mA
Internal backup battery:	-
Operation temp:	-35 °C 60 °C
Power supply:	$12 \text{ V DC} \pm 15\%$ (powering from external adapter)
Weight:	0.8 kg
Dimensions:	300 x 195 x 97 mm
Manufacturer / Brand:	SATEL
Guarantee:	2 years



SPL-2010-R