

Code: ASDC-12-124-HS

POE ADAPTER **ASDC-12-124-HS** ATTE

The ASDC-12-124-HS PoE adapter lowers the voltage on the DC plug to 12V and simultaneously transfers the PoE power supply to the RJ45 output. Thanks to this, from one PoE line we can simultaneously power the IP camera and additional devices powered by 12V DC.

The device can be powered from the 802.3af or PoE PASSIVE switch.



Output power:	max. 36 W (total)
Number of inputs:	1 pcs RJ-45
Input voltage:	35 ... 56 V DC - PoE
Output voltage:	• 35 ... 56 V DC - equal to the input voltage • 12 V DC - 2.1/5.5 mm plug on the cable
Output current:	max. 1 A @ 12 V DC
LED indicators:	DC output voltage presence indication
Main features:	Pin numbers for RJ-45 connector • 1/2, 3/6 Wires to data transmission • 4/5, 7/8 Power supply
Protections:	Overcurrent (overload) - automatic return to normal operation after the failure has ceased
Housing:	Plastic
Color:	Green
Operation temp:	-25 °C ... 40 °C
Weight:	0.02 kg
Dimensions:	73 x 21 x 17 mm
Manufacturer / Brand:	ATTE



DATA SHEET

Guarantee:

2 years