

Code: S-64H

SWITCH POE **S-64H** 4-PORT PULSAR

The S-64H switch is designed to supply IP cameras operating in the IEEE 802.3af/at standard. The device with the power supply adapter is enclosed in a housing with IP56 protection class. Four ports support Power over Ethernet (PoE) function.



LAN ports:	• 4 x RJ45 10/100 Base-TX - PoE (802.3af/at), • 2 x RJ45 10/100 Base-TX - Uplink ports
Management:	—
Transmission speed:	• 10 / 100 Mbps - 4 LAN & PoE ports, • 10 / 100 Mbps - 2 Uplink ports
Maximal output power:	30 W / port PoE
Maximal total power:	60 W
MAC addresses table:	1k
Operation modes:	• Extend On : 250 m, 10 Mbps @ UTP cat. 5e, 6 • Extend Off : 100 m, 100 Mbps @ UTP cat. 5e, 6
Main features:	There are cable glands in the housing : • 6 pcs Ø 4 ... 8 mm • 1 pcs Ø 10 ... 14 mm
Certificates:	CE
Power supply:	52 V DC / 1.15 A (power adapter included)
Housing:	Plastic, IP56



DATA SHEET

Weight:	1.25 kg
Dimensions:	148 x 240 x 80 mm
Manufacturer / Brand:	PULSAR
Guarantee:	2 years