

Code: RV-8/16-UHD/R

VIDEO SPLITTER **RV-8/16-UHD/R**

The RV-8/16-UHD/R splitter consists of 8 independent dual output video splitters. The modern design of the device enables cooperation with all standards commonly used in CCTV systems, operating in the band up to 120MHz. This means that the signal can be split in maximum resolution: AHD - 8Mpx, HD-CVI - 8Mpx, HD-TVI - 8Mpx, CVBS - 960H.

The design allows the module to be placed in the frame of the RACK 1U, 10" or 19" system. By combining two modules in a double frame, a 16/32 splitter can be obtained. The device is designed to continuous work in closed spaces.

The proper distances among sockets allow to easy BNC connectors mounting.



Standard:	<ul style="list-style-type: none"> • AHD / HD-CVI / HD-TVI - 8 Mpx 4K UHD, • CVBS - PAL, NTSC
Number of inputs:	8 pcs BNC
Number of outputs:	16 pcs BNC
Bandwidth:	0 ... 120 MHz (-3dB)
Inputs impedance:	75 Ω
Outputs impedance:	75 Ω
Input / Output protection:	ESD, IEC 61000-4-2, ± 30 kV contact, ± 30 kV airLightning, IEC 61000-4-5, 12A (tP=8/20 μ s)
Power supply:	7 ... 26 V DC (power adapter not included)
Current consumption:	60 mA @ 12 V DC
Gain :	0 dB
Weight:	0.13 kg
Dimensions:	218 x 40 x 22 mm (without stand)
Manufacturer / Brand:	DELTA
Guarantee:	5 years