

## DATA SHEET

Code: BCS-B-SP2402G-2SFP(II)

## SWITCH POE BCS-B-SP2402G-2SFP(II) 24-PORT SFP BCS BASIC

Due to reliability and ensuring high quality of transmission, the BCS-B-SP2402G-2SFP(II) 10/100  $\,$ Mb/s 24-port PoE desktop type switch is perfect solution for expanding home or office network. PoE powering possibility, compatible with the 802.3af / 802.3at standard makes the device more universal and easier to install.



LAN ports:	• 2 x port Combo: SFP (Base-X) / RJ45 (Base-T) • 24 x RJ45 ( 24 x PoE (802.3at) )
Management:	-
LED diodes:	Power, Act, PoE
Transmission speed:	• 10 / 100 Mbps - 24 LAN & PoE ports, • 10 / 100 / 1000 Mbps - 2 Uplink ports, • 1000 Mbps - 2 SFP ports
Maximal output power:	30 W / port PoE
Maximal total power:	250 W
Main features:	<ul> <li>2 x Port Uplink</li> <li>4 operating modes: AI VLAN, AI EXTEND, AI PoE, AI QoS - selectable by switch</li> <li>AI VLAN mode - ports 1 24 are isolated from ports 25, 26</li> <li>AI EXTEND mode - ports 1 8 support transmission up to 250 m (cat5e, cat6)</li> <li>AI QOS (Quality Of Service) mode - prioritization of video packets</li> <li>AI PoE mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected</li> </ul>
Certificates:	CE
Power supply:	100 240 V AC
Weight:	2.5 kg
Dimensions:	440 x 180 x 44 mm
Manufacturer / Brand:	BCS BASIC
Guarantee:	2 years

BCS-B-SP2402G-2SFP(II)

1/1