

Code: IPC-EB5541-AS

IP VANDALPROOF CAMERA **IPC-EB5541-AS** - 5 Mpx 1.4 mm - Fish Eye DAHUA

IP camera with "fish eye" wide-angle lens.
PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.



Standard:	TCP/IP
Sensor:	1/2.7 " Progressive Scan CMOS
Matrix size:	5 Mpx
Scanning system:	Progressive
Resolution:	2592 x 1944 - 5 Mpx , 2048 x 1536 - 3 Mpx , 1600 x 1200 - UXGA , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
Lens:	1.4 mm - Fish Eye / F2.6
View angle:	180 °
S/N ratio:	> 56 dB
RS-485 interface:	—
Image compression method:	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs:	1 / 1
Audio:	• Microphone built-in, • External microphone input, • Audio output, • Bi-directional audio streaming support
Main stream frame rate:	25 fps @ 5 Mpx
Network interface:	10/100 Base-T (RJ-45)



DATA SHEET

Network protocols:	IPv4/IPv6, HTTP, HTTPS, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, PPPoE, SNMP, IEEE 802.1x
Memory card slot:	Micro SD memory cards up to 256GB support (possible local recording)
Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Default IP address:	192.168.1.108
Default admin user / password:	admin / - The administrator password should be set at the first start
Web browser access ports:	80, 37777
PC client access ports:	37777
Mobile client access ports:	37777
Port ONVIF:	80
RTSP URL:	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
WEB Server:	Built-in
Max. number of on-line users:	20
ONVIF:	✓
Main features:	• WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • Possibility to change the resolution, quality and bit rate • Time mark and image description • Privacy zones - max. 4 • Motion Detection - max. 4 zones • Heat map - the selection in the image by corresponding colors the areas with different traffic • Configurable: brightness, contrast, saturation • IVS analysis : crossing the line (tripwire), intrusion, people counting - support for 4 independent detection areas
Power supply:	• PoE (802.3af), • 12 V DC / 280 mA
Power consumption:	≤ 5.1 W @ 12 V DC ≤ 6 W @ PoE
Housing:	Dome - Metal
Color:	White
"Index of Protection":	IP67
Vandal-proof:	IK10
Operation temp:	-30 °C ... 55 °C
Weight:	0.38 kg
Dimensions:	Ø 110 x 62 mm



DATA SHEET

Supported languages:	Polish, English
Manufacturer / Brand:	DAHUA
Guarantee:	3 years

