

Code: DS-K1T331W

ACCESS CONTROLLER WITH FACE RECOGNITION **DS-K1T331W** - 1080p Hikvision

Access controller with face recognition function.

Face recognition with extended functionality allows you to determine whether the observed person has a protective mask and in the absence of a mask perform the appropriate action, e.g. trigger a voice message reminding to cover the face.



Sensor:	CMOS
Matrix size:	2 Mpx
Resolution:	1920 x 1080 - 1080p

Access control:

Cards support:	Outdoor proximity cards and key-fobs reader
Face recognition distance:	0.3 m ... 1.5 m
Memory:	• Memory of 1000 face templates • Memory of 1500 RFID cards - after connecting an external RFID reader • Non-volatile log buffer of the last 150 000 events

General information:

Standard:	TCP/IP
IR illuminator:	—
LED illuminator:	✓
Video output:	—
RS-485 interface:	✓
Memory card slot:	—

Alarm inputs / outputs:	—
Audio:	Speaker built-in
Network interface:	• 10/100 Mb/s (RJ-45) • WiFi
Network protocols:	TCP/IP, ISUP, ISAPI
WEB Server:	Built-in
ONVIF:	—
Default IP address:	192.168.1.64
Default admin user / password:	admin / - The administrator password should be set at the first start
Web browser access ports:	80
PC client access ports:	port 8000
Main features:	• 3.97 " capacitive touch screen • Mechanical tamper protection • WDR - Wide Dynamic Range • AI detection : Face recognition • Configuration and management from the iVMS-4200 application • Port USB • Door lock control output • Possibility to connect an exit button and a reed switch to control the door status
Power supply:	12 V DC / 1.5 A (power adapter included)
Power consumption:	≤ 18 W
Housing:	Metal
Color:	Black / Silver
"Index of Protection":	—
Operation temp:	-10 °C ... 55 °C
Weight:	0.31 kg
Dimensions:	120 x 110 x 23 mm (without bracket)
Supported languages:	English, Spanish, Portuguese, Russian
Manufacturer / Brand:	Hikvision
SAP Code:	302912468
Guarantee:	3 years