

Code: XD-2-BR

MULTIPURPOSE WIRED DETECTOR **XD-2-BR** SATEL

The XD-2-BR wired detector can work in one of the 4 modes, which makes it an extremely universal device. Depending on your needs, the device can be configured as: magnetic detector, shock detector, shock detector with reed switch or water flood detector (FPX-1 external probe required - available separately).

The XD-2-BR works with any alarm control panel.



Support:	Alarm control panel
Detection:	Opening the door or window, Vibrations, Water
Environmental class EN 50130-5:	II
Protection class (Grade):	2
Sensitivity adjustment:	—
Alarm signaling:	LED indicator, Signal to control panel
Relay contacts rating (resistive load):	40 mA / 24 V DC
Power supply:	12 V DC / 14 mA (max)

Main features:	• Operation modes : - Magnetic detector - Opening the door or window - input for connecting a NC type wired detector - 1 Alarm output - Shock detector - Detection of shocks and vibrations associated with attempts to force a door or window - Range : 3 m - input for connecting a NC type wired detector - 1 Alarm output - Shock and magnetic detector - Detection of shocks and vibrations associated with attempts to force a door or window - Opening the door or window - input for connecting a NC type wired detector - 2 Alarm outputs - Water flood detector - The required FPX-1 probe is available separately - detecting the presence of water in spaces where there is a risk of leakage - 1 Alarm output • Tamper detection - opening the enclosure, removing from mounting surface • LED indication • Supply voltage control • 2 magnets included (for surface and flush mounting) • Compliance with EN 50130-4, EN 50130-5, EN 50131-1, EN 50131-2-6 standards
Color:	Brown
Operation temp:	-10 °C ... 55 °C
Weight:	0.023 kg
Dimensions:	• 20 x 102 x 23 mm (detector) • Ø 10 x 28 mm (magnet)
Manufacturer / Brand:	SATEL
Guarantee:	2 years