

Code: APTI-H54B

AHD, HD-CVI, HD-TVI, PAL CAMERA **APTI-H54B** - 8.3 Mpx, 4K UHD

Megapixel camera with 1/2.8" CMOS sensor and AHD / HD-CVI / HD-TVI / PAL.

The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in max. 8 Mpx (4K) resolution. During transmission there are no delays and is maintained the original, high quality image.

Setting the camera in PAL mode allows to obtain an image in 960H resolution. The change of the AHD / HD-CVI / HD-TVI / PAL standard is done with the corresponding button by keeping it pressed for approx. 5 seconds, without going into the OSD menu.



Standard:	AHD, HD-CVI, HD-TVI, PAL
Sensor:	1/2.8 " SONY Starvis™ Back-illuminated CMOS
Matrix size:	8.3 Mpx
Resolution:	3840 x 2160 - 8.3 Mpx, 4K UHD @ AHD / HD-CVI / HD-TVI @ 12.5 fps, 15 fps , 2592 x 1944 - 5 Mpx @ AHD / HD-CVI / HD-TVI, 20 fps , 2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 12.5 fps , 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 30 fps, 25 fps , 2560 x 1440 - 4 Mpx @ AHD @ 15 fps , 1920 x 1080 - 1080p @ AHD / HD-TVI / HD-CVI, 30 fps / 25 fps , 960 x 576 - 960H @ CVBS
Video output:	1 Vpp 75 Ω, AHD, HD-CVI, HD-TVI, PAL - selectable by buttons
Lens:	—
Auto Iris socket:	DC
Min. illumination:	0.001 Lux @ F1.2
IR illuminator support:	ICR - Movable InfraRed filter
Audio:	—
Alarm inputs / outputs:	—
RS-485 interface:	—

OSD menu:	✓
Main features:	• WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • Auto White Balance • AGC - Automatic Gain Control • Sharpness - sharper image outlines
Power supply:	12 V DC / 150 mA
Power consumption:	≤ 1.8 W
Housing:	BOX, Metal
Color:	White + Black
Operation temp:	-20 °C ... 60 °C
Weight:	0.54 kg
Dimensions:	149 x 82 x 58 mm
Supported languages:	English, Spanish, Portuguese
Manufacturer / Brand:	APTI
Guarantee:	2 years