

Code: SD6CE445XA-HNR

IP SPEED DOME CAMERA OUTDOOR **SD6CE445XA-HNR** - 4 Mpx 3.95 ... 177.7 mm DAHUA

IP camera equipped with very good high resolution sensor. Due to above it is perfect solution for surveillance systems requiring persons or vehicles recognition.

Built-in IR illuminator allows to operate at night conditions, and vari-focal lens with wide range of view angle adjustment enables optimal set the view field of camera to all conditions. The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).

For a few models of IP cameras working at $\geq 1920 \times 1080$ resolution we recommend to use of network with 1Gb/s bandwidth.

Thanks to the "Starlight" technology used, the camera only needs very low lighting to obtain a clear color image.



Standard:	TCP/IP
Sensor:	1/2.8 " STARVIS™ CMOS
Matrix size:	4 Mpx
Resolution:	2560 x 1440 - 4 Mpx , 2048 x 1536 - 3 Mpx , 1920 x 1080 - 1080p 1280 x 960 - 960p 1280 x 720 - 720p 704 x 576 - D1
Scanning system:	Progressive
Lens:	3.95 ... 177.7 mm
View angle:	• 70 ° ... 1.8 ° (manufacturer data) • 59 ° ... 1.8 ° (our tests result)
Optical zoom:	x 45
Digital zoom:	x 16
Range of IR illumination:	250 m



DATA SHEET

Video output:	—
Preset rotation speed:	max. 300 °/s (horizontal) max. 200 °/s (vertical)
Rotation speed (manual control):	0.1 °/s ... 260 °/s (horizontal) 0.1 °/s ... 120 °/s (vertical)
Horizontal rotation range:	360 ° continuous
Vertical rotation range:	-20 ° ... 90 °
RS-485 interface:	✓
Protocols:	Pelco-D, Pelco-P, DH-SD Auto detection
Number of presets:	300
Horizontal scan:	✓
Route settings:	8
Image compression method:	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs:	7 / 2
Audio:	• External microphone input • Audio output • Bi-directional audio streaming support
Main stream frame rate:	1 ... 25 fps - 4 Mpx
Memory card slot:	Micro SD memory cards up to 256GB support (possible local recording)
Network interface:	10BASE-T, 100BASE-TX (RJ-45)
Network protocols:	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, ARP, RTCP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS, Bonjour, IEEE 802.1x
WEB Server:	Built-in, NVR compliance
Max. number of on-line users:	20
ONVIF:	20.06
Mobile phones support:	Port 37777 • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Default IP address:	192.168.1.108
Default admin user / password:	admin / admin
Web browser access ports:	80, 37777
PC client access ports:	37777
Mobile client access ports:	37777
Port ONVIF:	80
RTSP URL:	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream

Main features:	• Intelligent Object Tracking • Power Up Action - execution the required camera function after power up • Park action - this function enables to locate the camera to specific position automatically if operator doesn't operate the controller for some time • Auto Flip - auto-rotates the camera during "tilt" type moving • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • EIS - Electronic Image Stabilization • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • Day/night mode • ICR - Movable InfraRed filter • WB - White Balance (ATW/AWB/manual/indoor/outdoor) • AGC - Automatic Gain Control • Sharpness - sharper image outlines • Motion Detection • Configurable Privacy Zones - 24 • The camera is equipped with a built-in heater with a thermostat • SMD PLUS - searching for an object classified as: human, motor vehicle, non-motor vehicle • Filtering of false alarms based on the recognition of persons and vehicles • Deep Learning technology • IVS analysis, crossing the line (tripwire), intrusion, abandoned/missing object, face detection
Power supply:	• PoE (802.3at), • 24 V DC / 1.1 A (power adapter included)
Power consumption:	≤ 26 W
Housing:	Speed Dome Metal
Color:	White
Vandal-proof:	IK10
"Index of Protection":	IP67
Operation temp:	-40 °C ... 70 °C
Weight:	6.6 kg (with bracket)
Dimensions:	209 x 302 x 417 mm (with bracket)
Supported languages:	Polish, English, Arabic, Czech, French, Spanish, Dutch, Korean, German, Portuguese, Russian, Italian
Manufacturer / Brand:	DAHUA
Guarantee:	3 years