DATA SHEET

Code: UNIFI-U6-LITE

ACCESS POINT **UNIFI-U6-LITE** UBIQUITI

The UBIQUITI UNIFI-U6-LITE is a device working in 2x2 MIMO (Multiple Input Multiple Output) standard.

The device is easy to use and manage. The distinguishing feature of the product is additional software UniFi WiFi Enterprise System, which enables configuration and management of the UniFi devices network, from computer via a web browser.

Frequency range:	2.4 GHz / 5 GHz
Antenna type:	2x2 MIMO, 2.4 GHz - 2.8 dBi / 5.0 GHz - 3 dBi, Integrated - 2 x Omnidirectional antenna
Standards:	• IEEE 802.11a, • IEEE 802.11b, • IEEE 802.11g, • IEEE 802.11n, • IEEE 802.11ac, • IEEE 802.11ax
Baud rates:	• 1201 Mbps @ 5 GHz, • 300 Mbps @ 2.4 GHz
Protections:	WEP, WPA-PSK, WPA-Enterprise (WPA/WPA2, TKIP/AES)
LAN ports:	1 x 10/100/1000 Mbps
Operating system:	UniFi WiFi Enterprise System
Transmitter power:	• 20 dBm @ 2.4 GHz (max) • 20 dBm @ 5.0 GHz (max)
Power supply PoE:	Ubiquiti Passive PoE
Power supply:	• PoE (802.3af), • 44 ... 57 V DC / 0.25 A - PoE Adapter (not included)

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Power consumption:	12 W
Main features:	• Possibility to mount on the wall or ceiling • UniFi WiFi Enterprise System • AP placement and RF maps • Easy and uniform management system for many devices • Intuitive installation and configuration of many advanced functions
Operation temp:	-30 °C ... 60 °C
Permissible relative humidity:	5 % ... 95 %
Weight:	0.33 kg
Dimensions:	Ø 160 x 31.5 mm
Manufacturer / Brand:	UBIQUITI
Guarantee:	2 years

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60