

Code: PFS4226-24ET-360-V3

SWITCH POE **PFS4226-24ET-360-V3** 24-PORT SFP DAHUA

Due to reliability and ensuring high quality of transmission, the PFS4226-24ET-360-V3 10/100 Mb/s 24-port PoE desktop type switch is perfect solution for expanding home or office network.

Attention! The SFP port requires the SFP module, which is available in our offer.



LAN ports:	• 24 x RJ45 - 10/100 Base-T (22 PoE (802.3af/at) + 2 Hi-PoE / PoE (802.3bt) / PoE (802.3af/at)), • 2 x port Combo: SFP (1000 Base-X) / RJ45 (10/100/1000 Base-T) - Uplink, • 1 x RJ45 - Console
Management:	✓
Transmission speed:	• Ethernet - 10 Mbps Full Duplex, • Fast Ethernet - 100 Mbps Full Duplex, • Gigabit Ethernet - 1000 Mbps Full Duplex (Uplink)
Maximal output power:	• 30 W / port PoE • 90 W / port Hi-PoE / PoE 802.3bt
Maximal total power:	360 W
Operation modes:	• Extend On : 250 m, 10 Mbps • Extend Off : 100 m, 100 Mbps
MAC addresses table:	4k

Main features:	• Switch is web managed • Intelligent management of Power Supply Unit power's output stage • Green PoE • protection against lightning discharges and voltage differences and strokes between devices • IEEE 802.1Q VLAN • Spanning Tree STP/RSTP • Data Flow Control (802.3x) • Port mirroring function • IGMP Snooping • DHCP client • Hardware supports IP + MAC binding based on port • MAC addresses filtering • IEEE 802.1x port authentication • QoS/DSCP priority based on IEEE 802.1p standard • Watchdog PoE • Ports marked in red support IEEE802.3af, IEEE802.3at, IEEE802.3bt and Hi-PoE standards with a maximum output power of 90 W per port - designed to power high power devices • Range PoE : 250 m @ 10 Mbps • The device supports 8-pin power supply • Console : RJ-45 output • RESET button
LED diodes:	Power : 50 % / 80 % / 100 %, Link, PoE, System
Certificates:	CE
Power supply:	100 ... 240 V AC
Housing type:	RACK 19", 1U
Operation temp:	-10 °C ... 55 °C
Weight:	3.38 kg
Dimensions:	440 x 300 x 44 mm
Manufacturer / Brand:	DAHUA
Guarantee:	5 years