

DATA SHEET

Code: NVR2108HS-I2 NVR NVR2108HS-I2 8 CHANNELS DAHUA



 $\ensuremath{\mathsf{NVR}}$ equipped with advanced functions of intelligent image analysis.

| Standard: | TCP/IP |
|-------------------------------------|---|
| Supported resolutions: | max. 12 Mpx |
| Video outputs: | 1 pcs HDMI 4K 1 pcs VGA |
| Audio support: | 8 Channels - Audio from cameras |
| Audio inputs: | 1 pcs CINCH |
| Audio outputs: | 1 pcs CINCH |
| Image compression method: | H.265+ / H.265 / H.264+ / H.264 / MJPEG |
| USB: | 2 pcs USB 2.0 |
| Supported hard drives: | 1 x 10 TB SATA III |
| Recording modes: | Manual, Sensor, Motion detection, Schedule |
| Network protocols: | HTTP, HTTPS, TCP/IP, IPv4/IPv6, RTSP, UDP, NTP, DHCP, DNS, SMTP, UPnP, IP Filter, DDNS, Alarm Server, P2P, ONVIF |
| External storage devices backup: | Backup to USB drive (pendrive, external drive) |
| Searching and playback the records: | Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) All channels synchronous playback, Smart Search function |
| Bitrate: | max. 80 Mbps |
| Network functions: | Full support via network, Remote records copying, Web Server built-in |



NVR2108HS-I2



DATA SHEET

| Mobile phones support: | Port no.: 37777 or access by a cloud (P2P) • Android: Free application <u>DMSS</u> • iOS (iPhone): Free application <u>DMSS</u> See how to configure the P2P function in Dahua recorders and how to enable the mobile application |
|-------------------------------------|--|
| Default IP address: | 192.168.1.108 |
| Default admin user / password: | admin / - The administrator password should be set at the first start |
| Web browser access ports: | 80, 37777 |
| PC client access ports: | 37777 |
| Mobile client access ports: | 37777 |
| RTSP URL: | rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream |
| Alarm inputs / outputs: | - |
| PTZ control: | IP Speed Dome Cameras |
| Motion Detection: | 22 x 18 motion zones - after motion detection records detected channels only |
| Intelligent Image Analysis: | × |
| Mouse support: | × |
| IR remote controller in the set: | - |
| Main features: | Advanced peripheral protection functions: intrusion, crossing line with separate rules for vehicles and pedestrians, classification of people and vehicles, Face recognition and analysis in real time (up to 12 photos per second) : Comparison of faces with images from the database Face analysis: determination of sex, age and characteristic elements of appearance (glasses, facial hair, mask) Real-time search of people on the basis of given side information in the range corresponding to features recognized by artificial intelligence of the device Support for up to 10 face databases, including 5000 face images Face bases can be used globally or locally for one video channel - depending on the need In the base other than face photography, can also be stored such information as: name, sex, date of birth, nationality, address, ID number |
| Power supply: | 12 V DC / 1.5 A (power adapter included) |
| Weight: | 0.83 kg |
| Dimension | 260 x 233 x 48 mm |
| Dimensions: | |
| Dimensions: Supported languages: | Polish, English, Bulgarian, Czech, Danish, Finnish, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Romanian, Slovenian, Serbian, Swedish, Hungarian, Italian |
| | German, Portuguese, Russian, Romanian, Slovenian, Serbian, Swedish, Hungarian, |



NVR2108HS-I2