

Code: TL-LS1005G

SWITCH **TL-LS1005G** 5-PORT TP-LINK

The device is widely used in small computer networks, neighborhood networks.



LAN ports:	5 x (RJ45) 10/100/1000 Mb Auto-Negotiation, Auto MDI/MDIX
Management:	—
LED diodes:	Power, Link/Act
Transmission speed:	10 / 100 / 1000 Mbps - Gigabit Ethernet
Jumbo Frame:	16 kB
MAC addresses table:	2 k
Main features:	• LiteWave product series • Auto MDI/MDX • Auto-learning and Auto-aging functions support for MAC addresses • Support for bandwidth control in full duplex (IEEE802.3x) and a back pressure function in half-duplex mode • Green TP-LINK technology - big energy saving • Box casing designed to wall mounting
Certificates:	CE, FCC, RoHS
Housing:	Plastic, Desktop
Power supply:	5 V DC / 600 mA (power adapter included)
Power consumption:	max. 3.7 W
Operation temp:	0 °C ... 40 °C
Permissible relative humidity:	10 % ... 90 %
Weight:	0.07 kg
Dimensions:	90 x 72 x 23 mm



DATA SHEET

Manufacturer / Brand:	TP-LINK
Guarantee:	3 years

