

Code: VT03312Q-P

VIDEO DOORPHONE **VT03312Q-P** DAHUA

Video Doorphone is mounted in a surface housing.

It is a hybrid module - it can work in a 2-Wire installation or as a standard IP video doorphone.



Compatibility:	DAHUA
Sensor:	1/2.8 ", 2 Mpx CMOS
View angle:	125 °
proximity reader built-in:	Access control cards - 13.56 MHz S50, Memory of 3000 RFID cards
Image compression method:	H.265 / H.264
LED illuminator:	—
IR illuminator:	✓
RS-485:	✓



Main features:	• The function of the monitor with the ability to open the door can be a smartphone, tablet or the VTH indoor panel, • Micro SD memory cards up to 256GB support (possible local recording), • Support up to 4 subscriber numbers, • Monitoring the status of individual doors, • WDR - 120 dB - Wide Dynamic Range, • 2D-DNR, 3D-DNR - Digital Noise Reduction, • Day/Night mode (color/b&w/auto), • ICR - Movable InfraRed filter, • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Noise suppression and echo cancellation, • Tamper detection - removing from mounting surface, • Vandal-proof front panel, • LED diodes, • Alarm inputs / outputs : 1 / 1, • Output for the additional lock release button, • Rain cover included
Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Power supply:	• 48 V / 1 A, • PoE (802.3af), • 2-Wire IP interface
Power consumption:	≤ 4 W (Standby mode) ≤ 8 W (operation)
Housing:	Aluminum
Color:	Graphite
"Index of Protection":	IP65
IK rating:	IK08
Operation temp:	-40 °C ... 60 °C
Weight:	0.6 kg
Dimensions:	• 188 x 107 x 30 mm (without cover) • 191 x 112 x 44 mm (with cover)
Supported languages:	Polish, English
Manufacturer / Brand:	DAHUA
Guarantee:	3 years