

## DATA SHEET

Code: APWK-LED

## EMERGENCY DOOR RELEASE BUTTON APWK-LED YOTOGI

The APWK-LED button has optical and acoustic signaling. Optical signaling is provided by LED diodes. LED indicators can have two colors - green (normal state) or red (alarm state). The operation of the red LED can be set in one of three ways - on / off / flashing. It is also possible to set the operating mode of the acoustic signaling - silent / intermittent / continuous and to set the intensity of the generated sound.



| Contact type:          | 3 x NO/NC  |
|------------------------|--|
| Relay maximal load:    | 3 A / 125 V  |
| Material:              | ABS  |
| "Index of Protection": | IP24   |
| Main features:         | <ul> <li>LED indication</li> <li>Sound signaling</li> <li>Alarm memory</li> <li>Key for opening the enclosure included</li> <li>Mount - Surface-mounted / Flush-mounted</li> </ul> |
| Power supply:          | • 12 V DC<br>• 24 V DC   |
| Current consumption:   | • 12 V : 18 mA (operation) / 75 mA (alarm)<br>• 24 V : 11 mA (operation) / 41 mA (alarm)   |
| Color:                 | Green  |
| Operation temp:        | -30 °C 70 °C   |
| Weight:                | 0.164 kg   |
| Dimensions:            | 90 x 93 x 45 mm  |
| Manufacturer / Brand:  | YOTOGI   |



## DATA SHEET

| Guarantee: | 2 years |
|------------|---------|