

Code: VTO2301R-P

VIDEO DOORPHONE **VTO2301R-P** IP DAHUA

The device works with video doorphones, and other DAHUA panels. Video Doorphone is mounted in a surface housing.

Attention! The doorphone has no controllable outputs.



Compatibility:	DAHUA
Sensor:	1/2.8 ", 2 Mpx CMOS
View angle:	110 °
Image compression method:	H.264 / H.265
IR illuminator:	✓
Resolution:	• Main stream : 1280 x 720, 800 x 480, 720 x 576, 352 x 288 • Sub stream : 1920 x 1080, 800 x 480, 720 x 576, 352 x 288
proximity reader built-in:	—
Network interface:	Ethernet 10 / 100 Mbps
The number of subscribers served:	1

Main features:	• It can only work with the mobile application, without the VTH monitor, • The function of the monitor can be a smartphone, tablet or VTH internal panel, • Micro SD memory cards up to 256GB support (possible local recording), • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Echo suppression and reduction / digital noise reduction, • Tamper detection - opening the enclosure, • WDR - 120 dB - Wide Dynamic Range, • 2D-DNR, 3D-DNR - Digital Noise Reduction
Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Power supply:	• PoE (802.3af), • 12 V DC / 500 mA
Power consumption:	• ≤ 5.5 W (operation) • ≤ 3.5 W (Standby mode)
Housing:	Aluminum alloy, Waterproof
Color:	Graphite
"Index of Protection":	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone
Operation temp:	-40 °C ... 60 °C
Weight:	0.24 kg
Dimensions:	170 x 57 x 35 mm
Supported languages:	Polish, English, Bulgarian, Czech, Finnish, Slovenian, Slovak, Hungarian
Manufacturer / Brand:	DAHUA
Guarantee:	3 years