

Code: PH-3

NETWORK ADAPTER **PH-3** Tenda

The PH-3 network transmitters kit is designed for Ethernet signal transmission through power line. Devices are an ideal solution when it is impossible to install UTP cables or the environment does not allow to use wireless connectivity.

Devices must be plugged into the outlets using the same branch (phase).



LAN ports:	1 pcs - LAN module
Standards:	HomePlug AV2, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab
Protections:	128-bit AES encryption
LED diodes:	Power supply, Power network, Ethernet
Transmission speed:	1000 Mbps @ Ethernet
Transmission range via electrical installation:	300 m - Within a building
Power supply:	100 ... 240 V AC, 50 / 60 Hz
Power consumption:	max. 3.2 W (operation) 0.38 W (Standby mode)
Main features:	• Plug & Play • QoS • IGMP Snooping • IPTV compliance • Optimization of the video streaming : 1 Gb/s 4K UHD • HomePlug AV 2 compliance • Pair / Reset button - Encryption activation • Operating frequency : 2 ... 86 MHz • Power-saving mode - Energy saving up to 88%
Certificates:	CE, FCC, RoHS
Operation temp:	0 °C ... 40
Weight:	0.1 kg (single element)
Dimensions:	82 x 60 x 70 mm (single element)



DATA SHEET

Manufacturer / Brand:	Tenda
Guarantee:	2 years