

Code: DL2-150-48-U

## SWITCHING ADAPTER **DL2-150-48-U**

Switching adapter installed on the TS35/7.5 or 15 DIN rail, resistant to high operation temperatures (up to 70°C).



|                            |                                                                                                                                     |
|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Adapter type:              | Switching                                                                                                                           |
| Power voltage:             | <ul style="list-style-type: none"> <li>• 85 ... 264 V AC</li> <li>• 120 ... 370 V DC</li> </ul>                                     |
| Output voltage:            | 48 V DC                                                                                                                             |
| Output voltage adjustment: | 43.2 ... 55.2 V DC                                                                                                                  |
| Maximal load:              | <ul style="list-style-type: none"> <li>• 2.7 A @ 100 ... 120 V AC,</li> <li>• 3.2 A @ 200 ... 240 V AC</li> </ul>                   |
| Output power:              | <ul style="list-style-type: none"> <li>• 130 W @ 100 ... 120 V AC,</li> <li>• 153 W @ 200 ... 240 V AC</li> </ul>                   |
| Number of outputs:         | 2 pcs                                                                                                                               |
| Efficiency:                | 91 %                                                                                                                                |
| Housing type:              | DIN                                                                                                                                 |
| Protections:               | <ul style="list-style-type: none"> <li>• Short-circuit</li> <li>• Overload</li> <li>• Overvoltage</li> <li>• Temperature</li> </ul> |



## DATA SHEET

|                                      |                                |
|--------------------------------------|--------------------------------|
| Operation temp. / Relative humidity: | -30 °C ... 70 °C / 10 ... 95 % |
| Weight:                              | 0.34 kg                        |
| Dimensions:                          | 105 x 89 x 58 mm               |
| Guarantee:                           | <b>3 years</b>                 |