

Code: KW-10/6X80

## EXPANSION PLUG **KW-10/6X80** KLIMAS

Expansion plug for solid substrates with countersunk head screw.

The expansion plug is designed for fixing of light-duty interior finish systems, wood members and lightweight installations or mounting clamps on solid substrates.

Types of substrates for installation: plain concrete of class not lower than C20/25 (PN-EN 206/1:2003), solid clay brick of class not lower than 15 (PN-EN 771-1:2011), aerated concrete of variety 600, class 5 (PN-EN 771-4:2011) and solid sand-lime brick of class 20 (PN-EN 771-2:2011).



|                        |                                                                                                                           |
|------------------------|---------------------------------------------------------------------------------------------------------------------------|
| Material:              | <ul style="list-style-type: none"> <li>• Expansion plug, Polypropylene</li> <li>• Screw, Steel galvanized</li> </ul>      |
| Drilling diameter:     | 10 mm                                                                                                                     |
| Expansion plug length: | 60 mm                                                                                                                     |
| Screw dimensions:      | Ø 6 x 80 mm, PZ-3                                                                                                         |
| Application:           | <ul style="list-style-type: none"> <li>• Concrete</li> <li>• Solid clay brick</li> <li>• Solid sand-lime brick</li> </ul> |
| Manufacturer / Brand:  | KLIMAS                                                                                                                    |
| Guarantee:             | 2 years                                                                                                                   |

